



I. Introduction

An owner or operator may fill in this form in replacement of a highlighted copy of the New Source Performance Standard (NSPS) located in 40 CFR 60, Subpart I - Standards of Performance for Hot Mix Asphalt Facilities.

Please be aware that all facilities subject to this NSPS are also subject to 40 CFR 60 Subpart A - General Provisions. Where this NSPS refers to portions of Subpart A (§60.1 to §60.19), please copy those referenced portions of Subpart A and check off the specific items that apply to your facility.

You can find the most recent version of 40 CFR 60, subpart A on EPA's website at <http://www.epa.gov/epacfr40/chapt-I.info/chi-toc.htm/>. A formatted version of subpart A (Form NSPS-A) with check off boxes is available on the MPCA's website, at <http://www.pca.state.mn.us/air/permits/forms.html>.

NSPS PROVISION	<input checked="" type="checkbox"/> if APPLICABLE
Location and Language	
Section 60.90 Applicability and designation of affected facility.	<input type="checkbox"/>
(a) The affected facility to which the provisions of this subpart apply is each hot mix asphalt facility. For the purpose of this subpart, a hot mix asphalt facility is comprised only of any combination of the following: dryers; systems for screening, handling, storing, and weighing hot aggregate; systems for loading, transferring, and storing mineral filler, systems for mixing hot mix asphalt; and the loading, transfer, and storage systems associated with emission control systems.	<input type="checkbox"/>
(b) Any facility under paragraph (a) of this section that commences construction or modification after June 11, 1973, is subject to the requirements of this subpart.	<input type="checkbox"/>
Section 60.91 Definitions.	<input type="checkbox"/>
As used in this subpart, all terms not defined herein shall have the meaning given them in the Act and in subpart A of this part.	
(a) <i>Hot mix asphalt facility</i> means any facility, as described in §60.90, used to manufacture hot mix asphalt by heating and drying aggregate and mixing with asphalt cements.	
Section 60.92 Standard for particulate matter.	<input type="checkbox"/>
(a) On and after the date on which the performance test required to be conducted by §60.8 is completed, no owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any affected facility any gases which:	<input type="checkbox"/>
(1) Contain particulate matter in excess of 90 mg/dscm (0.04 gr/dscf).	<input type="checkbox"/>
(2) Exhibit 20 percent opacity, or greater.	<input type="checkbox"/>
Section 60.93 Test methods and procedures.	<input type="checkbox"/>
(a) In conducting the performance tests required in §60.8, the owner or operator shall use as reference methods and procedures the test methods in appendix A of this part or other methods and procedures as specified in this section, except as provided in §60.8(b).	<input type="checkbox"/>
(b) The owner or operator shall determine compliance with the particulate matter standards in §60.92 as follows:	<input type="checkbox"/>
(1) Method 5 shall be used to determine the particulate matter concentration. The sampling time and sample volume for each run shall be at least 60 minutes and 0.90 dscm (31.8 dscf).	<input type="checkbox"/>
(2) Method 9 and the procedures in §60.11 shall be used to determine opacity.	<input type="checkbox"/>