

**AIR EMISSION PERMIT NO. 08300038-006
(MAJOR AMENDMENT)**

IS ISSUED TO

ADM CORN PROCESSING-MARSHALL

400 West Erie Road
Marshall, Lyon County, MN 56258

The emission units, control equipment and emission stacks at the stationary source authorized in this permit are as described in the following permit applications:

Permit Type	Application Date	Permit Number
Total Facility Operating Permit	01/17/1995	08300038-001
Major Amendment	1/16/2001	08300038-002
Major Amendment	08/27/2001	08300038-003
Major Amendment	MPCA-initiated	08300038-004
Administrative Amendment	10/28/02	08300038-005
Major Amendment	11/6/02: MPCA initiated	08300038-006

This permit amends Air Emission Permit No. 08300038-005, and authorizes the Permittee to operate the stationary source at the address listed above unless otherwise noted in Table A. The Permittee must comply with all the conditions of the permit. Any changes or modifications to the stationary source must be performed in compliance with Minn. R. 7007.1150 to 7007.1500. Terms used in the permit are as defined in the state air pollution control rules unless the term is explicitly defined in the permit.

Permit Type: Federal; Part 70/Major for NSR

Major Amendment

Issue Date: August 8, 2000

Issue Date: November 7, 2003

Expiration August 8, 2005

Title I Conditions Do Not Expire

Ann M. Foss
Major Facilities Section Manager
Majors and Remediation Division

for Sheryl A. Corrigan
Commissioner
Minnesota Pollution Control Agency

TABLE OF CONTENTS

Notice to the Permittee

Permit Shield

Facility Description

Table A: Limits and Other Requirements

Table B: Submittals

Appendices: Modeling Parameters
Insignificant Activities Required to be Listed

NOTICE TO THE PERMITTEE:

Your stationary source may be subject to the requirements of the Minnesota Pollution Control Agency’s (MPCA) solid waste, hazardous waste, and water quality programs. If you wish to obtain information on these programs, including information on obtaining any required permits, please contact the MPCA general information number at:

Metro Area	(651) 296-6300
Outside Metro Area	1-800-657-3864
TTY	(651) 282-5332

The rules governing these programs are contained in Minn. R. chs. 7000-7105. Written questions may be sent to: Minnesota Pollution Control Agency, 520 Lafayette Road North, St. Paul, Minnesota 55155-4194.

Questions about this air emission permit or about air quality requirements can also be directed to the telephone numbers and address listed above.

PERMIT SHIELD:

Subject to the limitations in Minn. R. 7007.1800, compliance with the conditions of this permit shall be deemed compliance with the specific provision of the applicable requirement identified in the permit as the basis of each condition.

Subject to the limitations of Minn. R. 7007.1800 and 7017.0100, subp. 2, notwithstanding the conditions of this permit specifying compliance practices for applicable requirements, any person (including the Permittee) may also use other credible evidence to establish compliance or non-compliance with applicable requirements.

FACILITY DESCRIPTION:

Minnesota Corn Processors, LLC (MCP) is a wet corn mill and ethanol production plant. The existing stationary source includes equipment for receiving, cleaning, storing, and milling corn. The source also includes equipment for the generation of steam and the production of corn syrup, cornstarch, and high fructose corn syrup.

The MCP facility is a major source under the federal Part 70 permit program, and a major source of particulate matter, nitrogen oxides, sulfur dioxide, and carbon monoxide under the federal Prevention of Significant Deterioration program.

Amendment 1 (Air Emission Permit No. 08300038-002) to the permit authorized a change in the required scrubber pH, and incorporated a performance test schedule.

Amendment 2 (Air Emission Permit No. 08300038-003) to the permit changed the changed the pressure drop ranges required for four of the pieces of control equipment.

Amendment 3 (Air Emission Permit No. 08300038-004) incorporates operating parameters set as a result of operating conditions during stack testing on December 6, 2001.

Amendment 4 (Air Emission Permit No. 08300038-005) transfers the ownership for the ADM Corn Processing-Marshall (formerly Minnesota Corn Processors LLC).

Amendment 5 (Air Emission Permit No. 08300038-006) is a MPCA-initiated major amendment under Minn. R. 7007.1600, subp. 1(D) – mandatory reopening that is needed in order to assure compliance with applicable requirements. The amendment incorporates new limits into the permit. The limits are imposed through performance testing under Minn. R. 7017.2025, subp. 3, for Stack/Vent 011 (gluten dryer emissions) as stated in a letter dated November 6, 2002 to Archer Daniels Midland.

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Table A contains limits and other requirements with which your facility must comply. The limits are located in the first column of the table (What To do). The limits can be emission limits or operational limits. This column also contains the actions that you must take and the records you must keep to show that you are complying with the limits. The second column of Table A (Why to do it) lists the regulatory basis for these limits. Appendices included as conditions of your permit are listed in Table A under total facility requirements.

Subject Item: Total Facility

What to do	Why to do it
A. FACILITY SPECIFIC REQUIREMENTS	hdr
Parameters Used in Modeling: The stack heights, stack diameters, air flow rates, and exhaust gas temperatures used in the modeling performed for the PSD analysis for this permit are listed in Appendix I of this permit. The Permittee must submit to the Agency for approval any revisions of these parameters that are caused by a physical change or change in the method of operation of the facility and must wait for a written approval before making such changes. The information submitted must include, at a minimum, the locations, heights and diameters of the stacks, locations and dimensions of nearby buildings, the velocity and temperature of the gases emitted, and the PM10, SO2, NOX, and CO emission rates. The plume dispersion characteristics after the proposed revisions must be equivalent to or better than the dispersion characteristics used in the model dated February 29, 2000. The Permittee shall demonstrate this equivalency in the proposal.	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
If the information submitted does not demonstrate equivalent or better dispersion characteristics, or if a conclusion cannot readily be made about the dispersion, the Permittee must remodel. For any physical change to or change in the method of operation of a stack emitting PM10 or for any increase in PM10 emissions (whether or not the increase would require a permit amendment of any type), the Permittee must remodel. For changes that do not involve any increase to any emission rate or any emissions from a new emission point, this proposal must be submitted as soon as practicable, but no less than 60 days before beginning actual construction of the modification, stack, or associated emission unit(s).	Title I Condition, continued from above...
For changes involving increases in emission rates or emissions from a new emission point and that require a minor permit amendment, the proposal and/or required modeling analysis must be submitted as soon as practicable, but no less than 60 days before beginning actual construction of the modification, stack, or associated emission unit(s). For changes involving increases in emission rates or emissions from a new emission point and that require a permit amendment other than a minor amendment, the proposal and/or modeling analysis must be submitted with the permit application.	Title I Condition, continued from above...
B. GENERAL REQUIREMENTS	hdr
Operation and Maintenance Plan: Retain at the stationary source an operation and maintenance plan for all air pollution control equipment. The plan must include a maintenance schedule.	Minn. R. 7007.0800, subp. 14 and Minn. R. 7007.0800, subp. 16(J)
Operation and Maintenance of Control Equipment: The Permittee shall conduct all necessary maintenance and make all necessary attempts to keep all pollution control equipment in proper operating condition at all times. The Permittee shall operate and maintain the control equipment according to the manufacturer's specifications or the Operation and Maintenance Plan developed by the Permittee.	Title I Condition: Monitoring for 40 CFR Section 52.21 (j) or (k)
Permittee Inspection of Control Equipment: The Permittee shall inspect all control equipment according to manufacturer's specifications or the Operation and Maintenance Plan developed by the Permittee, and maintain a written record of the inspection and any action resulting from the inspection.	Minn. R. 7007.0800, subp. 2 and subp. 14
Performance Testing: Conduct all performance tests in accordance with Minn. R. ch. 7017 unless otherwise noted in Tables A, B, and/or C.	Minn. R. ch. 7017
Limits set as a result of a performance test (conducted before or after permit issuance) apply until superseded as specified by Minn. R. 7017.2025 following formal review of a subsequent performance test on the same unit.	Minn. R. 7017.2025

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

<p>General Performance Test (PT) Requirements:</p> <p>Performance Tests are due as outlined in Tables A and B of the permit. See Table B for additional testing requirements.</p> <p>PT Notifications (written): due 30 days before each Performance Test PT Plan: due 30 days before each Performance Test PT Pre-test Meeting: due 7 days before each Performance Test PT Report: due 45 days after each Performance Test PT Report-Microfiche: due 105 days after each Performance Test</p>	<p>Minn. R. 7017.2030, subp. 1, subp. 1-4 and Minn. R. 7017.2035, subp. 1-2</p>
<p>Monitoring Equipment: Install or make needed repairs to monitoring equipment within 60 days of issuance of the permit if monitoring equipment is not installed and operational on the date the permit is issued.</p>	<p>Minn. R. 7007.0800, subp. 4(D)</p>
<p>Monitoring Equipment Calibration: Annually calibrate all required monitoring equipment (any requirements applying to continuous emission monitors are listed separately in this permit).</p>	<p>Minn. R. 7007.0800, subp. 4(D)</p>
<p>Operation of Monitoring Equipment: Unless otherwise noted in Tables A, B, and/or C, monitoring a process or control equipment connected to that process is not necessary during periods when the process is shutdown, or during checks of the monitoring systems, such as calibration checks and zero and span adjustments. If monitoring records are required, they should reflect any such periods of process shutdown or checks of the monitoring system.</p>	<p>Minn. R. 7007.0800, subp. 4(D)</p>
<p>Circumvention: Do not install or use a device or means that conceals or dilutes emissions, which would otherwise violate a federal or state air pollution control rule, without reducing the total amount of pollutant emitted.</p>	<p>Minn. R. 7011.0020</p>
<p>Shutdown Notifications: Notify the Commissioner at (651)296-7300 at least 24 hours in advance of a planned shutdown of any control equipment or process equipment if the shutdown would cause any increase in the emissions of any regulated air pollutant. If the owner or operator does not have advance knowledge of the shutdown, notification shall be made to the Commissioner as soon as possible after the shutdown. However, notification is not required in the circumstances outlined in Items A, B and C of Minn. R. 7019.1000, subp. 3.</p> <p>At the time of notification, the owner or operator shall inform the Commissioner of the cause of the shutdown and the estimated duration. The owner or operator shall notify the Commissioner when the shutdown is over.</p>	<p>Minn. R. 7019.1000, subp. 3</p>
<p>Breakdown Notifications: Notify the Commissioner at (651)296-7300 within 24 hours of a breakdown of more than one hour duration of any control equipment or process equipment if the breakdown causes any increase in the emissions of any regulated air pollutant. The 24-hour time period starts when the breakdown was discovered or reasonably should have been discovered by the owner or operator. However, notification is not required in the circumstances outlined in Items A, B and C of Minn. R. 7019.1000, subp. 2.</p> <p>At the time of notification or as soon as possible thereafter, the owner or operator shall inform the Commissioner of the cause of the breakdown and the estimated duration. The owner or operator shall notify the Commissioner when the breakdown is over.</p>	<p>Minn. R. 7019.1000, subp. 2</p>
<p>Notification of Deviations Endangering Human Health or the Environment: As soon as possible after discovery, notify the MPCA or the state duty officer, either orally or by facsimile, of any deviation from permit conditions which could endanger human health or the environment.</p> <p>MPCA: (651)296-7300 State Duty Officer: (651)649-5451 or (800)422-0798</p>	<p>Minn. R. 7019.1000, subp. 1</p>
<p>Notification of Deviations Endangering Human Health or the Environment Report: Within 2 working days of discovery, notify the Commissioner in writing of any deviation from permit conditions which could endanger human health or the environment. Include the following information in this written description:</p> <ol style="list-style-type: none"> 1. the cause of the deviation; 2. the exact dates of the period of the deviation, if the deviation has been corrected; 3. whether or not the deviation has been corrected; 4. the anticipated time by which the deviation is expected to be corrected, if not yet corrected; and 5. steps taken or planned to reduce, eliminate, and prevent reoccurrence of the deviation. 	<p>Minn. R. 7019.1000, subp. 1</p>
<p>Operation Changes: In any shutdown, breakdown, or deviation the Permittee shall immediately take all practical steps to modify operations to reduce the emission of any regulated air pollutant. The Commissioner may require feasible and practical modifications in the operation to reduce emissions of air pollutants. No emissions units that have an unreasonable shutdown or breakdown frequency of process or control equipment shall be permitted to operate.</p>	<p>Minn. R. 7019.1000, subp. 4</p>

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

<p>Air Pollution Control Equipment: Operate all pollution control equipment whenever the corresponding process equipment and emission units are operated, unless otherwise noted in Table A.</p>	<p>Minn. R. 7007.0800, subp. 2; Minn. R. 7007.0800, subp. 16(J)</p>
<p>Fugitive Emissions: Do not cause or permit the handling, use, transporting, or storage of any material in a manner which may allow avoidable amounts of particulate matter to become airborne. Comply with all other requirements listed in Minn. R. 7011.0150.</p>	<p>Minn. R. 7011.0150</p>
<p>Application for Permit Amendment: If a permit amendment is needed, submit an application in accordance with the requirements of Minn. R. 7007.1150 through Minn. R. 7007.1500. Submittal dates vary, depending on the type of amendment needed. All changes involving any requirement identified as a Title I Condition require a major amendment.</p> <p>Submit all applications to the Air Quality Permit Technical Advisor, Minnesota Pollution Control Agency, Metro District/Major Facilities, 520 Lafayette Road North, St. Paul, MN 55155</p>	<p>Minn. R. 7007.1150 through Minn. R. 7007.1500</p>
<p>Extension Requests: The Permittee may apply for an Administrative Amendment to extend a deadline in a permit by no more than 120 days, provided the proposed deadline extension meets the requirements of Minn. R. 7007.1400, subp. 1(H).</p> <p>Submit all permit and amendment applications to the Air Quality Permit Technical Advisor, Minnesota Pollution Control Agency, Metro District/Major Facilities, 520 Lafayette Road North, St. Paul, MN 55155</p>	<p>Minn. R. 7007.1400, subp. 1(H)</p>
<p>Recordkeeping: Maintain records describing any insignificant modifications (as required by Minn. R. 7007.1250, subp. 3) or changes contravening permit terms (as required by Minn. R. 7007.1350 subp. 2), including records of the emissions resulting from those changes.</p>	<p>Minn. R. 7007.0800, subp. 5(B)</p>
<p>Record keeping: Retain all records at the stationary source or at the corporate offices in Marshall, MN, for a period of five (5) years from the date of monitoring, sample, measurement, or report. Records which must be retained at this location include all calibration and maintenance records, all original recordings for continuous monitoring instrumentation, and copies of all reports required by the permit. Records must conform to the requirements listed in Minn. R. 7007.0800, subp. 5(A).</p>	<p>Minn. R. 7007.0800, subp. 5(C)</p>
<p>Noise: The Permittee shall comply with the noise standards set forth in Minn. R. 7030.0010 to 7030.0080 at all times during the operation of any emission units. This is a state only requirement and is not enforceable by the EPA Administrator or citizens under the Clean Air Act.</p>	<p>Minn. R. 7030.0010 - 7030.0080</p>
<p>The Permittee shall comply with the General Conditions listed in Minn. R. 7007.0800, subp. 16.</p>	<p>Minn. R. 7007.0800, subp. 16</p>
<p>Inspections: The permittee shall comply with the inspection procedures and requirements as found at Minn. R. 7007.0800, subp 9(A).</p>	<p>Minn. R. 7007.0800, subp. 9(A)</p>
<p>Emissions Inventory Report: due April 1 of each year. To be submitted on a form approved by the Commissioner.</p>	<p>Minn. R. 7019.3000 through Minn. R. 7019.3010</p>
<p>Emission Fees: due 60 days after receipt of an MPCA bill.</p>	<p>Minn. R. 7002.0005 through Minn. R. 7002.0095</p>
<p>Insignificant Activities Required to be Listed: Appendix II includes activities and sources at the facility that have been determined to be insignificant under Minn. R. 7007.1300. This list is not all-inclusive; it is subject to change.</p> <p>The Permittee shall properly maintain the sources listed in Appendix II, to prevent excessive amounts of pollutants from being emitted from them.</p>	<p>Minn. R. 7007.0800, subp. 2; Minn. R. 7007.1300</p>

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: GP 001 Corn Silos 1-6

- Associated Items:** SV 025 Corn Silo #1
 SV 026 Corn Silo #2
 SV 027 Corn Silo #3
 SV 028 Corn Silo #4
 SV 031 Corn Silo #5
 SV 032 Corn Silo #6

What to do	Why to do it
A. EMISSION LIMITS (Apply individually to each of SV025, SV026, SV027, SV028, SV031, SV032)	hdr
Total Particulate Matter: less than or equal to 0.07 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Particulate Matter < 10 micron: less than or equal to 0.07 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.010 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 10 percent opacity	Minn. R. 7011.1005, subp. 3(D)
Opacity: less than or equal to 5 percent opacity from fugitive emissions from each unit (emissions directly from the unit, not collected by ductwork to the fabric filter)	Minn. R. 7011.1005, subp. 3(A)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check each stack (outlets of CE063, CE064, CE065, CE066, CE067, and CE068) for any visible emissions, or, during inclement weather, read and record pressure drop across the baghouse two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
C. EMISSION UNIT OPERATION (EU101 - EU106)	hdr
The Permittee shall clean up commodities spilled on the driveway and other facility property as required to minimize fugitive emissions to a level consistent with RACT (reasonably available control technology).	Minn. R. 7011.1005, subp. 1(A)
D. CONTROL EQUIPMENT OPERATION (CE063, CE064, CE065, CE066, CE067, CE068 - fabric filters)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control equipment required to meet modeling limits)
Total Particulate Matter: greater than or equal to 80 percent control efficiency	Minn. R. 7011.1005, subp 3(E)
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 10.0 inches of water column (for each baghouse)	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: GP 002 Sources of Fugitive Particulate Matter

Associated Items: FS 003 Vehicle Traffic (paved roads)

FS 004 Coal Pile & Coal transfer operations

What to do	Why to do it
<p>Do not cause or permit the transporting of any material in a manner which may allow avoidable amounts of particulate matter to become airborne.</p> <p>Do not cause or permit a road or a driveway to be constructed, used, repaired, or demolished without applying all such reasonable measures as may be required to prevent particulate matter from becoming airborne. Take reasonable precautions to prevent the discharge of visible fugitive dust emissions beyond the lot line of the property on which the emissions originate. The commissioner may require such reasonable measures as may be necessary to prevent particulate matter from becoming airborne, including but not limited to, paving or frequent clearing of roads, driveways, and parking lots; application of dust-free surfaces; application of water; and the planting and maintenance of vegetative ground cover.</p>	<p>Minn. R. 7011.0150</p>

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 001 Old Corn Receiving Area

Associated Items: EU 001 Old Corn Receiving Pit (multiple components)

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.88 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by citizens.	Minn. R. 7009.0020
Particulate Matter < 10 micron: less than or equal to 0.88 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.009 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 10 percent opacity	Minn. R. 7011.1005, subp. 3(D)
Opacity: less than or equal to 5 percent opacity from fugitive emissions (emissions directly from the receiving pit, not collected by ductwork to the fabric filter)	Minn. R. 7011.1005, subp. 3(A)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE001) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, once each day of operation of EU001.	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
C. EMISSION UNIT OPERATION (EU001)	hdr
Clean up commodities spilled on the driveway and other facility property as required to minimize fugitive emissions.	Minn. R. 7011.1005, subp. 1(A)
EU001 shall not be operated between the hours of 8:00 p.m. and 6:00 a.m.	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
EU001 may not be operated simultaneously with EU003.	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Recordkeeping: Each day, record the date, and the times of all truck traffic through the corn receiving area.	Title I Condition: Recordkeeping for 40 CFR Section 52.21(k) limits
Recordkeeping: Each day of operation of this unit, record the date and the times of operation.	Title I Condition: Recordkeeping for 40 CFR Section 52.21(k) limits
Recordkeeping: The Permittee shall keep complete descriptions of each piece of equipment described by EU001. The description shall include the manufacturer, model number, capacity, and date of original installation. The description shall also identify each piece of equipment using a unique identification (ID) number. The Permittee shall submit updated versions of these descriptions with the annual Equipment List submittal (see Table B).	Title I Condition: Recordkeeping for 40 CFR Section 52.21 (k) (changes covered by modeling limits)
The Permittee may make changes to the equipment in the receiving pit, provided the changes are in compliance with all permit requirements. Changes allowed may include replacing individual components with similar components, moving or changing the configuration of components, or adding new components of the type listed in the most recently submitted Equipment List (see Table B). If a change would increase the capacity of the operation, trigger an applicable limit that is not contained in this permit, or would cause the existing emission limits to be unachievable, or would cause the emission of a different regulated pollutant (other than particulate matter), the change must go through the appropriate procedures under Minn. R. ch. 7007. If a change would require an increase in the PM10 emission limit or would cause the emission of a pollutant other than particulate matter, the facility must be modeled according to the methods required under 40 CFR Section 52.21(l).	Title I Condition: 40 CFR 52.21(k) (changes covered by modeling limits)
D. CONTROL EQUIPMENT OPERATION (CE001 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control required to meet modeling limit)
Total Particulate Matter: greater than or equal to 80 percent control efficiency	Minn. R. 7011.1005, subp 3(E)
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 8.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

<p>Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.</p>	<p>Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit</p>
--	---

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 002 New Corn Receiving Area

Associated Items: EU 003 Corn Receiving (multiple components)

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 3.62 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Particulate Matter < 10 micron: less than or equal to 3.62 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.010 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 10 percent opacity	Minn. R. 7011.1005, subp. 3(D)
Opacity: less than or equal to 5 percent opacity from fugitive emissions (emissions directly from the receiving pit, not collected by ductwork to the fabric filter)	Minn. R. 7011.1005, subp. 3(A)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE060) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Performance Test: due before end of each 60 months starting 01/31/2003 to measure (1)total particulate matter emissions and (2)PM10 emissions at the stack. The first test is due January 31, 2003, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1)Title I Condition: Testing for 40 CFR Section 52.21(j) limit (2) Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits (1&2) Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU003)	hdr
Clean up commodities spilled on the driveway and other facility property as required to minimize fugitive emissions.	Minn. R. 7011.1005, subp. 1(A)
EU003 shall not be operated between the hours of 8:00 p.m. and 6:00 a.m.	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
EU003 may not be operated simultaneously with EU001.	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Recordkeeping: The Permittee shall keep complete descriptions of each piece of equipment described by EU003. The description shall include the manufacturer, model number, capacity, and date of original installation. The description shall also identify each piece of equipment using a unique identification (ID) number. The Permittee shall submit updated versions of these descriptions with the annual Equipment List submittal (see Table B).	Title I Condition: 40 CFR Section 52.21(j) & (k) (Recordkeeping of changes covered under BACT and modeling limits)
The Permittee may make changes to the receiving equipment, provided the changes are in compliance with all permit requirements. Changes allowed may include replacing individual components with similar components, moving or changing the configuration of components, or adding new components of the type listed in the most recently submitted Equipment List (see Table B). If a change would increase the capacity of the operation, trigger an applicable limit that is not contained in this permit, or would cause the existing emission limits to be unachievable, or would cause the emission of a different regulated pollutant (other than particulate matter), the change must go through the appropriate procedures under Minn. R. ch. 7007. If a change would require an increase in the PM10 emission limit or cause the emission of a pollutant other than particulate matter, the facility must be modeled according to the methods required under 40 CFR Section 52.21(l).	Title I Condition: 40 CFR 52.21(j) & (k) (changes covered by BACT and modeling limits)
D. CONTROL EQUIPMENT OPERATION (CE060 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: CFR Section 52.21(j) (BACT for EU003); 40 CFR Section 52.21(k)
Total Particulate Matter: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) [Also meets the requirements of Minn. R. 7011.1005, subp. 3(E)]
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

<p>Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.</p>	<p>Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)</p>
--	---

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 003 Corn Cleaner Transfer

Associated Items: EU 004 Corn Cleaner Transfer (multiple components)

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.71 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Particulate Matter < 10 micron: less than or equal to 0.71 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.010 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 10 percent opacity	Minn. R. 7011.1005, subp. 3(D)
Opacity: less than or equal to 5 percent opacity from fugitive emissions (emissions directly from EU004, not collected by ductwork to the fabric filter)	Minn. R. 7011.1005, subp. 3(A)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE004) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Performance Test: due before end of each 60 months starting 09/26/2005 to measure (1) total particulate matter and (2) PM10 emissions at the stack. The first test is due September 26, 2005, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1) Title I Condition: Testing for 40 CFR Section 52.21(j) limit (2) Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits and Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU004)	hdr
Recordkeeping: The Permittee shall keep complete descriptions of each piece of equipment described by EU004. The description shall include the manufacturer, model number, capacity, and date of original installation. The description shall also identify each piece of equipment using a unique identification (ID) number. The Permittee shall submit updated versions of these descriptions with the Annual Equipment List Submittal (see Table B).	Title I Condition: 40 CFR 52.21(j) & (k) (changes covered by BACT and modeling limits)
The Permittee may make changes to the corn cleaner transfer equipment, provided the changes are in compliance with all permit requirements. Changes allowed may include replacing individual components with similar components, moving or changing the configuration of components, or adding new components of the type listed in the most recently submitted Equipment List (see Table B). If a change would increase the capacity of the operation, trigger an applicable limit that is not contained in this permit, or would cause the existing emission limits to be unachievable, or would cause the emission of a different regulated pollutant (other than particulate matter), the change must go through the appropriate procedures under Minn. R. ch. 7007. If a change would require an increase in the PM10 emission limit or would cause the emission of a pollutant other than particulate matter, the facility must be modeled according to the methods required under 40 CFR Section 52.21(l).	Title I Condition: 40 CFR 52.21(j) & (k) (changes covered by BACT and modeling limits)
Process Throughput: less than or equal to 509.7 tons/hour using 24-hour Block Average of corn, based on a 56 pound bushel. This is equivalent to 18,204 bushels per hour. Downtime of 15 minutes or more is not to be counted as operating time.	Minn. R. 7017.2025
Recordkeeping of Throughput: Each day, calculate the amount of corn processed for the previous day, in bushels per hour. Divide the total amount of corn by the hours of operating time. Do not count downtime of 15 minutes or more as operating time.	Minn. R. 7007.0800, subp. 5
D. CONTROL EQUIPMENT OPERATION (CE004 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: CFR Section 52.21(j) (BACT for EU004); 40 CFR Section 52.21(k)
Total Particulate Matter: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) [Also meets the requirements of Minn. R. 7011.1005, subp. 3(E)]
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 004 Corn Cleaner

Associated Items: EU 005 Corn Cleaner

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.46 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Particulate Matter < 10 micron: less than or equal to 0.46 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.010 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 10 percent opacity	Minn. R. 7011.1005, subp. 3(D)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE044) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Performance Test: due before end of each 60 months starting 09/26/2005 to measure (1) total particulate matter and (2) PM10 emissions at the stack. The first test is due September 26, 2005, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1) Title I Condition: Testing for 40 CFR Section 52.21(j) limit (2) Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits and Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU005)	hdr
Process Throughput: less than or equal to 537.94 tons/hour using 24-hour Block Average of corn, based on a 56 pound bushel. This is equivalent to 19,212 bushels per hour. Downtime of 15 minutes or more is not to be counted as operating time.	Minn. R. 7017.2025
Recordkeeping of Throughput: Each day, calculate the amount of corn processed for the previous day, in bushels per hour. Divide the total amount of corn by the hours of operating time. Do not count downtime of 15 minutes or more as operating time.	Minn. R. 7007.0800, subp. 5
D. CONTROL EQUIPMENT OPERATION (CE044 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: CFR Section 52.21(j) (BACT for EU005); 40 CFR Section 52.21(k)
Total Particulate Matter: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) [Also meets the requirements of Minn. R. 7011.1005, subp. 3(E)]
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 005 Fines Storage Bin

Associated Items: EU 006 Fines Storage Bin

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.06 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Particulate Matter < 10 micron: less than or equal to 0.06 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.012 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 10 percent opacity	Minn. R. 7011.1005, subp. 3(D)
Opacity: less than or equal to 5 percent opacity from fugitive emissions (emissions directly from the bin, not collected by ductwork to the fabric filter)	Minn. R. 7011.1005, subp. 3(A)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE062) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Performance Test: due before end of each 60 months starting 09/26/2005 to measure (1) total particulate matter and (2) PM10 emissions at the stack. The first test is due September 26, 2005, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1) Title I Condition: Testing for 40 CFR Section 52.21(j) limit (2) Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits and Minn. R. Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU006)	hdr
The Permittee shall clean up commodities spilled on the driveway and other facility property as required to minimize fugitive emissions to a level consistent with RACT (reasonably available control technology).	Minn. R. 7011.1005, subp. 1(A)
Process Throughput: less than or equal to 48950 bushel/hour using 24-hour Block Average of corn fines. Downtime of 15 minutes or more is not to be counted as operating time.	Minn. R. 7017.2025
Recordkeeping of Throughput: Each day, calculate the amount of corn fines processed for the previous day, in bushels per hour. Divide the total amount of corn fines by the hours of operating time. Do not count downtime of 15 minutes or more as operating time.	Minn. R. 7007.0800, subp. 5
D. CONTROL EQUIPMENT OPERATION (CE062 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: CFR Section 52.21(j) (BACT for EU006); 40 CFR Section 52.21(k)
Total Particulate Matter: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) [Also meets the requirements of Minn. R. 7011.1005, subp. 3(E)]
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 006 Millhouse Equipment

Associated Items: EU 007 Existing Millhouse equipment (multiple components)

EU 008 New Millhouse equipment (multiple components)

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 6.00 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 6.00 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.014 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
Sulfur Dioxide: less than or equal to 14.97 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each 60 months starting 09/26/2005 to measure (1) total particulate matter and (2) PM10 emissions at the stack. The first test is due September 26, 2005, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1)Title I Condition: Testing for 40 CFR Section 52.21(j) limit (2)Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits and (1&2) Minn. R. 7017.2020, subp. 1
Performance Test: due before end of each 60 months starting 07/31/2003 to measure SO2 emissions at the stack. The tests shall be conducted at an interval not to exceed 60 months between test dates. The first test is due July 31, 2003, then every 60 months thereafter. For additional applicable performance test requirements, see 'General Performance Test Requirements' in Table A, Subject Item "Total Facility".	Title I Condition: Testing for 40 CFR Section 52.21(j) & (k) limits and Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU007, EU008)	hdr
Recordkeeping: The Permittee shall keep complete descriptions of each piece of equipment described by EU007 and EU008. The description shall include the manufacturer, model number, capacity, and date of original installation. The description shall also identify each piece of equipment using a unique identification (ID) number. The Permittee shall submit updated versions of these descriptions with the annual Equipment List submittal (see Table B).	Title I Condition: 40 CFR 52.21(j) & (k) (changes covered by BACT and modeling limits)
The Permittee may make changes to the milling equipment, provided the changes are in compliance with all permit requirements. Changes allowed may include replacing individual components with similar components, moving or changing the configuration of components, or adding new components of the type listed in the most recently submitted Equipment List (see Table B). If a change would increase the capacity of the operation, trigger an applicable limit that is not contained in this permit, or would cause the existing emission limits to be unachievable, or would cause the emission of a different regulated pollutant (other than particulate matter or SO2), the change must go through the appropriate procedures under Minn. R. ch. 7007. If a change would require an increase in the PM10 or SO2 emission limit or would cause the emission of a pollutant other than particulat matter or SO2, the facility must be modeled according to the methods required under 40 CFR Section 52.21(l).	Title I Condition: 40 CFR 52.21(j) & (k) (changes covered by BACT and modeling limits)
D. CONTROL EQUIPMENT OPERATION (CE045 - packed gas absorption column)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: CFR Section 52.21(j) (BACT for EU008); 40 CFR Section 52.21(k)
Total Particulate Matter: greater than or equal to 90 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j)
Particulate Matter < 10 micron: greater than or equal to 90 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Sulfur Dioxide: greater than or equal to 70 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Pressure Drop: greater than or equal to 0.5 inches of water column and less than or equal to 8.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Water flow rate: greater than or equal to 850 gallons/minute and less than or equal to 1300 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
pH of scrubbing liquid: greater than or equal to 8.0	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Pressure Drop: Once each operating day, read and record pressure drop.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Water Flow Rate: Once each operating day, read and record the water flow rate.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Scrubber Water pH: Once each operating day, read and record the ph.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Corrective Actions: If the recorded pressure drop, water flow rate, or scrubber water ph is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for CE045 and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: **SV 007 Starch Dryer**

Associated Items: EU 009 Starch Dryer #1

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.04 grains/dry standard cubic foot	Title I Condition: To avoid classification of a previous modification as major under 40 CFR Section 52.21 [Also meets the requirements of Minn. R. 7011.0715, subp. 1(A)]
Total Particulate Matter: less than or equal to 7.94 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Particulate Matter < 10 micron: less than or equal to 0.024 grains/dry standard cubic foot	Title I Condition: To avoid classification of a previous modification as major under 40 CFR Section 52.21
Particulate Matter < 10 micron: less than or equal to 7.94 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.009 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
Sulfur Dioxide: less than or equal to 23.93 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each 60 months starting 01/31/2003 to measure (1)total particulate matter, (2)PM10, and (3)SO2 emissions at the stack. The first test is due January 31, 2003, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1) Testing for Minn. R. 7009.0200 limit; (1&2) Title I Condition: Testing for synthetic minor limits; (2&3) Title I Condition: Testing for 40 CFR Section 52.21(k) limits; (1,2,&3) Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU009) - N/A	hdr
D. CONTROL EQUIPMENT OPERATION (CE006 - spray tower)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: CFR Section 52.21(k) (use of control required to meet modeling limits)
Total Particulate Matter: greater than or equal to 20 percent control efficiency	Title I Condition: Control required to avoid classification of a previous modification as major under 40 CFR Section 52.21
Particulate Matter < 10 micron: greater than or equal to 20 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Sulfur Dioxide: greater than or equal to 70 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 1.0 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Water flow rate: greater than or equal to 400 gallons/minute and less than or equal to 600 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
pH of scrubber water: greater than or equal to 2.0 and less than or equal to 6.0	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Pressure Drop: Once each operating day, read and record pressure drop.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Water Flow Rate: Once each operating day, read and record the water flow rate.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Scrubber Water pH: Once each operating day, read and record the scrubber water pH.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Corrective Actions: If the recorded pressure drop, water flow rate, or pH is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for CE006 and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 008 Product Loadout

Associated Items: EU 010 Bin #1

EU 011 Bin #2

EU 012 Bin #3

EU 013 Bin #4

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.35 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.35 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.010 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE011) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, once each day of operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
C. EMISSION UNIT OPERATION (EU010 - EU013) - N/A	hdr
D. CONTROL EQUIPMENT OPERATION (CE011 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: CFR Section 52.21(k) (use of control required to meet modeling limit)
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 12.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 009 Germ Dryer

Associated Items: EU 015 Germ Dryer #1

EU 017 Germ Dryer #2

EU 019 Germ Dryer #3

EU 020 Germ Dryer #4

EU 022 Germ Dryer #5

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 2.5 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 2.5 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.016 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
Sulfur Dioxide: less than or equal to 5.98 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each 60 months starting 01/31/2003 to measure (1) total particulate matter, (2) PM10, and (3) SO2 emissions at the stack. The first test is due January 31, 2003, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1) Testing for 7009.0200 and 7011.0715 limits; (2&3) Title I Condition: Testing for 40 CFR Section 52.21(k) limits; (1,2,&3) Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU015, EU017, EU019, EU020, EU022) - N/A	hdr
D. CONTROL EQUIPMENT OPERATION (CE012 - spray tower)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: CFR Section 52.21(k) (use of control required to meet modeling limits)
Particulate Matter < 10 micron: greater than or equal to 20 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Sulfur Dioxide: greater than or equal to 70 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.5 inches of water column and less than or equal to 6.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Water flow rate: greater than or equal to 800 gallons/minute and less than or equal to 1400 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Scrubber water pH: greater than or equal to 6.0 and less than or equal to 8.0	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Pressure Drop: Once each operating day, read and record pressure drop.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Water Flow Rate: Once each operating day, read and record the water flow rate.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of scrubber water pH: Once each operating day, read and record the scrubber water pH.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Corrective Actions: If the recorded pressure drop, water flow rate, or pH is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for CE012 and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 010 Feedhouse Equipment

Associated Items: EU 064 Existing Feedhouse Equipment (multiple components)

EU 065 New Feedhouse Equipment (multiple components)

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 6.00 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 6.00 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.014 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
Sulfur Dioxide: less than or equal to 8.98 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each 60 months starting 01/31/2003 to measure (1)total particulate matter, (2)PM10, and (3)SO2 emissions at the stack. The first test is due January 31,2003, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1)Title I Condition: Testing for 40 CFR Section 52.21(j) limit (2&3) Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits (1-3) Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU064, EU065)	hdr
Recordkeeping: The Permittee shall keep complete descriptions of each piece of equipment described by EU064 and EU065. The description shall include the manufacturer, model number, capacity, and date of original installation. The description shall also identify each piece of equipment using a unique identification (ID) number. The Permittee shall submit updated versions of these descriptions with the annual Equipment List submittal (see Table B).	Title I Condition: 40 CFR 52.21(j) & (k) (changes covered by BACT and modeling limits)
The Permittee may make changes to the feedhouse equipment, provided the changes are in compliance with all permit requirements. Changes allowed may include replacing individual components with similar components, moving or changing the configuration of components, or adding new components of the type listed in the most recently submitted Equipment List (see Table B). If a change would increase the capacity of the operation, trigger an applicable limit that is not contained in this permit, or would cause the existing emission limits to be unachievable, or would cause the emission of a different regulated pollutant (other than PM, PM10, or SO2), the change must go through the appropriate procedures under Minn. R. ch. 7007. If a change would require an increase in the PM10 or SO2 emission limit or would cause the emission of a pollutant other than particulate matter or SO2, the facility must be modeled according to the methods required under 40 CFR Section 52.21(l).	Title I Condition: 40 CFR 52.21(j) & (k) (changes covered by BACT and modeling limits)
D. CONTROL EQUIPMENT OPERATION (CE046 - packed gas absorption column)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: CFR Section 52.21(j) (BACT for new feedhouse equipment, EU065)
Total Particulate Matter: greater than or equal to 90 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j)
Particulate Matter < 10 micron: greater than or equal to 90 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Sulfur Dioxide: greater than or equal to 70 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Pressure Drop: greater than or equal to 0.5 inches of water column and less than or equal to 8.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Water flow rate: greater than or equal to 600 gallons/minute and less than or equal to 850 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
pH of scrubbing liquid: greater than or equal to 8.0	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Pressure Drop: Once each operating day, read and record pressure drop.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Recordkeeping of Water Flow Rate: Once each operating day, read and record the water flow rate.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Scrubber Water pH: Once each operating day, read and record the pH.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Corrective Actions: If the recorded pressure drop, water flow rate, or scrubber water pH is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for CE045 and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: **SV 011 Gluten Dryer**

Associated Items: EU 028 Gluten Dryer #1

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 17.5 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0610, subp. 1(A)(1)
Particulate Matter < 10 micron: less than or equal to 17.5 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.019 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity , except for one six-minute period per hour of not more than 60 percent opacity.	Minn. R. 7011.0610, subp. 1(A)(2)
Sulfur Dioxide: less than or equal to 15.0 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Nitrogen Oxides: less than or equal to 3.07 lbs/hour using an annual average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Carbon Monoxide: less than or equal to 90.06 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each 36 months starting 09/02/2002 to measure (1)NOx, and (2)CO emissions at the stack. Initial performance testing was completed on 9/02/02.	(1-2)Title I Condition: Testing for 40 CFR Section 52.21(j) & (k) limits (1-2) Minn. R. 7017.2020, subp. 1
For additional applicable performance test requirements, see 'General Performance Test Requirements' in Table A, Subject Item "Total Facility".	
Performance Test: due before end of each 60 months starting 12/06/2005 to measure (1) total particulate matter emissions, (2) PM10 emissions, and (3) SO2 emissions at the stack. The first test is due December 6, 2005, then every 60 months thereafter.	(1) Title I Condition: Testing for 40 CFR Section 52.21(j) & Minn. R. 7011.0610 limits; (2-3) Title I Condition: Testing for 40 CFR Section 52.21(j) & (k) limits; (1-3) Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU028)	hdr
Fuel Use: Limited to natural gas only.	Title I Condition: 40 CFR Section 52.21(j) (BACT for NOx, CO)
Process Throughput: less than or equal to 30910 lbs/hour using 30-day Rolling Average of dried gluten. Downtime of 15 minutes or more is not to be counted as operating time.	Minn. R. 7017.2025
Recordkeeping of Throughput: Each day, calculate the amount of gluten loaded into railcars for the previous day and for the previous 30-day period. Divide the total amount of gluten loaded for the previous 30-day period by the hours of operating time during the previous 30-day period. Do not count downtime of 15 minutes or more as operating time.	Minn. R. 7007.0800, subp. 5
D. CONTROL EQUIPMENT OPERATION (CE021 - spray tower)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: CFR Section 52.21(j) (BACT for PM, PM10, SO2)
Total Particulate Matter: greater than or equal to 20 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j)
Particulate Matter < 10 micron: greater than or equal to 20 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Sulfur Dioxide: greater than or equal to 70 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Pressure Drop: greater than or equal to 1.0 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Water flow rate: greater than or equal to 600 gallons/minute and less than or equal to 1200 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
pH of scrubber water: greater than or equal to 6.0 and less than or equal to 8.0	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Pressure Drop: Once each operating day, read and record pressure drop.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Water Flow Rate: Once each operating day, read and record the water flow rate.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Recordkeeping of Scrubber Water pH: Once each operating day, read and record the pH.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Corrective Actions: If the recorded pressure drop, water flow rate, or pH is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for CE021 and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 012 Carbon Furnace #1

Associated Items: EU 034 Carbon Furnace #1

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 1.7 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0610, subp. 1(A)(1)
Particulate Matter < 10 micron: less than or equal to 1.7 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.040 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity , except for one six-minute period per hour of not more than 60 percent opacity.	Minn. R. 7011.0610, subp. 1(A)(2)
Sulfur Dioxide: less than or equal to 1.11 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Nitrogen Oxides: less than or equal to 1.87 lbs/hour using an annual average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Carbon Monoxide: less than or equal to 223.0 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each 36 months starting 01/09/2004 to measure particulate matter emissions at the stack. The first test is due January 9, 2004, and every 36 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	Testing for Minn. R. 7009.0200 and 7011.0610 limits; Minn. R. 7017.2020, subp. 1
Performance Test: due before end of each 60 months starting 02/28/2003 to measure NOX and SO2 emissions at the stack. The first test is due February 28, 2003, then every 60 months thereafter. For additional applicable performance test requirements, see 'General Performance Test Requirements' in Table A, Subject Item "Total Facility".	Title I Condition: Testing for 40 CFR Section 52.21(k) limit; Minn. R. 7017.2020, subp. 1
Performance Test: due before end of each 36 months starting 01/09/2004 to measure PM10 emissions at the stack. The first test is due January 9, 2004, then every 36 months thereafter. For additional applicable performance test requirements, see 'General Performance Test Requirements' in Table A, Subject Item "Total Facility".	Title I Condition: Testing for 40 CFR Section 52.21(k) limits; Minn. R. 7017.2020, subp. 1
Performance Test: due before end of each 60 months starting 01/09/2006 to measure CO emissions at the stack. The first test is due January 9, 2006, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	Title I Condition: Testing for 40 CFR Section 52.21(k) limits; Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU034)	hdr
Process Throughput: less than or equal to 1086.5 lbs/hour using 24-hour Block Average of regenerated carbon. Downtime of 15 minutes or more is not to be counted as operating time.	Minn. R. 7017.2025
Recordkeeping of Throughput: Each day, calculate the previous day's usage rate of regenerated carbon, in pounds per hour. Divide the total pounds of regenerated carbon by the hours of operating time. Do not count downtime of 15 minutes or more as operating time.	Minn. R. 7007.0800, subp. 5
D. CONTROL EQUIPMENT OPERATION (CE027 - venturi scrubber)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control equipment required to meet modeling limit)
Particulate Matter < 10 micron: greater than or equal to 90 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 2.0 inches of water column and less than or equal to 25.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Water flow rate: greater than or equal to 25 gallons/minute and less than or equal to 40 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Pressure Drop: Once each operating day, read and record pressure drop.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Water Flow Rate: Once each operating day, read and record the water flow rate.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Corrective Actions: If the recorded pressure drop or water flow rate is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for CE027 and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 013 Carbon Furnace #2

Associated Items: EU 035 Carbon Furnace #2

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.7 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0610, subp. 1(A)(1)
Particulate Matter < 10 micron: less than or equal to 0.7 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.007 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity , except for one six-minute period per hour of not more than 60 percent opacity.	Minn. R. 7011.0610, subp. 1(A)(2)
Sulfur Dioxide: less than or equal to 2.00 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Nitrogen Oxides: less than or equal to 3.38 lbs/hour using an annual average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Carbon Monoxide: less than or equal to 4.86 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each 60 months starting 03/01/2006 to measure (1)total particulate matter, (2)PM10, (3)SO2, and (4)NOx emissions at the stack. The first test is due on or before March 1, 2006, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1)Title I Condition: Testing for 40 CFR Section 52.21(j) limit (2-5)Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits (1-5) Minn. R. 7017.2020, subp. 1
Performance Test: due before end of each 36 months starting 03/01/2004 to measure CO emissions at the stack. The first test is due on or before March 1, 2004, then every 36 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1)Title I Condition: Testing for 40 CFR Section 52.21(j) limit (2-5)Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits (1-5) Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU035)	hdr
Fuel Use: Limited to natural gas only.	Title I Condition: 40 CFR Section 52.21(j) (BACT for NOX, CO, & SO2)
Process Throughput: less than or equal to 1649.46 lbs/hour using 24-hour Block Average of regenerated carbon. Down time of 15 minutes or more is not to be counted as operating time.	Minn. R. 7017.2025
Recordkeeping: Each day, calculate the previous day's usage rate of regenerated carbon, in pounds per hour. Divide the total pounds of regenerated carbon by the hours of operating time. Do not count downtime of 15 minutes or more as operating time.	Minn. R. 7007.0800, subp. 5
D. CONTROL EQUIPMENT OPERATION (CE028 - venturi/impinjet scrubber)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(j) (BACT for PM, PM10)
Total Particulate Matter: greater than or equal to 90 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j)
Particulate Matter < 10 micron: greater than or equal to 90 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Venturi Pressure Drop: greater than or equal to 10.0 inches of water column and less than or equal to 30.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Venturi Water flow rate: greater than or equal to 25 gallons/minute and less than or equal to 40 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Impinjet Pressure Drop: greater than or equal to 1.0 inches of water column and less than or equal to 15.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Impinjet Water flow rate: greater than or equal to 175 gallons/minute and less than or equal to 250 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Pressure Drop: Once each operating day, read and record the venturi and impinjet pressure drop.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Recordkeeping of Water Flow Rate: Once each operating day, read and record the venturi and impinjet water flow rates.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Corrective Actions: If the recorded pressure drops or water flow rates are outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for CE028 and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 014 Carbon Furnace #3

Associated Items: EU 036 Carbon Furnace #3

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.7 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0610, subp. 1(A)(1)
Particulate Matter < 10 micron: less than or equal to 0.7 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.007 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity , except for one six-minute period per hour of not more than 60 percent opacity.	Minn. R. 7011.0610, subp. 1(A)(2)
Sulfur Dioxide: less than or equal to 2.00 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Nitrogen Oxides: less than or equal to 3.38 lbs/hour using an annual average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Carbon Monoxide: less than or equal to 4.86 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each 60 months starting 01/11/2006 to measure (1) SO ₂ , (2) NO _x , (3) CO, (4) total particulate matter and (5) PM ₁₀ emissions at the stack. The first test is due January 11, 2006, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1)Title I Condition: Testing for 40 CFR Section 52.21(j) limit (2-5)Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits (1-5) Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU036)	hdr
Fuel Use: Limited to natural gas only.	Title I Condition: 40 CFR Section 52.21(j) (BACT for NO _x , CO, & SO ₂)
Process Throughput: less than or equal to 2087.5 lbs/hour using 24-hour Block Average of regenerated carbon. Down time of 15 minutes or more is not to be counted as operating time.	Minn. R. 7017.2025
Recordkeeping: Each day, calculate the previous day's usage rate of regenerated carbon, in pounds per hour. Divide the total pounds of regenerated carbon by the hours of operating time. Do not count downtime of 15 minutes or more as operating time.	Minn. R. 7007.0800, subp. 5
D. CONTROL EQUIPMENT OPERATION (CE029 - venturi/impinjet scrubber)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(j) (BACT for PM, PM ₁₀)
Total Particulate Matter: greater than or equal to 90 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j)
Particulate Matter < 10 micron: greater than or equal to 90 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Venturi Pressure Drop: greater than or equal to 10.0 inches of water column and less than or equal to 30.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Venturi Water flow rate: greater than or equal to 25 gallons/minute and less than or equal to 40 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Impinjet Pressure Drop: greater than or equal to 1.0 inches of water column and less than or equal to 15.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Impinjet Water flow rate: greater than or equal to 175 gallons/minute and less than or equal to 250 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Pressure Drop: Once each operating day, read and record the venturi and impinjet pressure drops.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Water Flow Rate: Once each operating day, read and record the venturi and impinjet water flow rates.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

<p>Recordkeeping of Corrective Actions: If the recorded pressure drops or water flow rates are outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for CE029 and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.</p>	<p>Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)</p>
--	---

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 015 Ethanol Plant Scrubbers

- Associated Items:** EU 037 A Pre-Fermenter
 EU 038 B Pre-Fermenter
 EU 039 1A Fermenter
 EU 040 2A Fermenter
 EU 041 2B Fermenter
 EU 042 1B Fermenter
 EU 043 3A Fermenter
 EU 044 3B Fermenter
 EU 045 4A Fermenter
 EU 046 4B Fermenter
 EU 047 Distillation/Dehydration #1
 EU 048 Distillation/Dehydration #2
 EU 060 Beer Well

What to do	Why to do it
A. EMISSION LIMITS	hdr
Sulfur Dioxide: less than or equal to 0.52 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each 60 months starting 07/17/2001 to measure sulfur dioxide emissions at the stack. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	Title I Condition: Testing for 40 CFR Section 52.21(k) limit and Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU037 - EU048, EU060)	hdr
Ethanol Production: less than or equal to 140536 gallons/day using 24-hour Block Average	Minn. R. 7017.2025, subp. 3
D. CONTROL EQUIPMENT OPERATION (CE030 & CE031 - packed gas absorption columns)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control required to meet modeling limit)
Sulfur Dioxide: greater than or equal to 70 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Combined Pressure Drop: greater than or equal to 1.0 inches of water column and less than or equal to 22.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Water flow rate: greater than or equal to 60 gallons/minute and less than or equal to 150 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Pressure Drop: Once each operating day, read and record pressure drop.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Water Flow Rate: Once each operating day, read and record the water flow rate.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Corrective Actions: If the recorded pressure drop or water flow rate is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for CE030 or CE031 (as appropriate) and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 016 Coal Boilers

Associated Items: EU 049 Coal Boiler #1

EU 050 Coal Boiler #2

MR 001 SO2 Monitor (Coal Boilers)

MR 002 O2 Monitor (Coal Boilers)

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.10 lbs/million Btu heat input using 24-hour Block Average (18 lbs/hour)	Title I Condition: To avoid classification of a previous modification as major under 40 CFR Section 52.21
Total Particulate Matter: less than or equal to 0.4 lbs/million Btu heat input	Minn. R. 7011.0515, subp. 1
Particulate Matter < 10 micron: less than or equal to 0.06 lbs/million Btu heat input using 24-hour Block Average	Title I Condition: To avoid classification of a previous modification as major under 40 CFR Section 52.21
Particulate Matter < 10 micron: less than or equal to 10.81 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity , except for one six-minute period per hour of not more than 60 percent opacity. (An exceedance of this opacity standard occurs whenever any one-hour period contains two or more six-minute periods during which the average opacity exceeds 20 percent or whenever any one-hour period contains one or more six-minute periods during which the average opacity exceeds 60 percent.)	Minn. R. 7011.0515, subp. 2
Sulfur Dioxide: less than or equal to 161.8 lbs/hour using 30-day Rolling Average	Title I Condition: To avoid classification of a previous modification as major under 40 CFR Section 52.21
Sulfur Dioxide: less than or equal to 252.22 lbs/hour using 1-Hour Average (= 1.4 lb/million Btu heat input)	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Sulfur Dioxide: less than or equal to 4 lbs/million Btu heat input using 1-Hour Average	Minn. R. 7011.0515, subp. 1
Nitrogen Oxides: less than or equal to 68.93 lbs/hour using an annual average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Carbon Monoxide: less than or equal to 47.94 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each 60 months starting 01/31/2003 to measure CO emissions at the stack. The first test is due on or before January 31, 2003, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	Title I Condition: Testing for 40 CFR Section 52.21(k) limit and Minn. R. 7017.2020, subp. 1, 7017.2030, subp. 4
Performance Test: due before end of each 36 months starting 12/31/2001 to measure NOx emissions at the stack. The first test is due on or before December 31, 2001, then every 36 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	Title I Condition: Testing for 40 CFR Section 52.21(k) limit and Minn. R. 7017.2020, subp. 1
Emissions Monitoring: The owner or operator shall use a CEMS to measure sulfur dioxide emissions from the boilers.	Title I Condition: Monitoring of emissions to avoid classification of a previous modification as major under 40 CFR Section 52.21; Minn. R. 7017.1006
C. EMISSION UNIT OPERATION (EU049, EU050)	hdr
Fuel Usage: less than or equal to 51996 tons/year using 12-month Rolling Sum , of coal	Title I Condition: To avoid classification of a previous modification as major under 40 CFR Section 52.21
Recordkeeping: By the 15th day of each month, calculate and record the quantity of coal used during the previous month, and during the previous 12 months (12-month rolling sum).	Title I Condition: To avoid classification of a previous modification as major under 40 CFR Section 52.21
Sulfur Content of Fuel: less than or equal to 1 percent by weight	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Recordkeeping: For each shipment of coal received, maintain records of the sulfur content of the shipment. Records may consist of certification from the coal supplier, or results of an analysis of a sample from the shipment.	Title I Condition: Recordkeeping for 40 CFR Section 52.21(j)
D. CONTROL EQUIPMENT OPERATION (CE032 & CE034 - multiple cyclones; CE033 & CE035 - fabric filters)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control required to meet modeling limit)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Total Particulate Matter: greater than or equal to 99.8 percent control efficiency	Title I Condition: Control required to avoid classification of a previous modification as major under 40 CFR Section 52.21
Particulate Matter < 10 micron: greater than or equal to 99.8 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
CE032 and CE034 Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
CE033 and CE035 Pressure Drop: greater than or equal to 0.5 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping: Once each operating day, read and record the pressure drop.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Corrective Actions: If the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for CE032, CE033, CE034, or CE035 (as appropriate) and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit
E. MONITOR OPERATING REQUIREMENTS (MR001)	hdr
The sulfur dioxide continuous monitoring system (CEMS) shall be operated and data recorded during all periods of operation of the boiler including startup, shutdown and malfunction, except for periods of acceptable monitor downtime. This requirement applies whether or not a numerical emission limit applies during these periods. A CEMS must not be bypassed except in emergencies where failure to bypass would endanger human health, safety, or plant equipment. Acceptable monitor downtime includes reasonable periods as listed in Items A, B, C and D of Minn. R. 7017.1090, subp. 2.	40 CFR Section 60.13(e)(6); Minn. R. 7017.1090, subp. 1
QA Plan: Develop and implement a written quality assurance plan that covers each CEMS. The plan shall be on site and available for inspection 30 days after monitor certification. The plan shall contain all of the information required by 40 CFR Section 60, Appendix F, section 3.	Minn. R. 7017.1170, subp. 2
CEMS Daily Calibration Drift (CD) Test: The CD shall be quantified and recorded at zero (low level) and upscale (high-level) gas concentrations at least once daily. The CEMS shall be adjusted whenever the CD exceeds twice the specification of 40 CFR 60, Appendix B. 40 CFR 60, Appendix F, shall be used to determine out-of-control periods for CEMS.	Minn. R. 7017.1170, subp. 3
Recordkeeping: The owner or operator must retain records of all CEMS monitoring data and support information for a period of five years from the date of the monitoring sample, measurement, or report. Records shall be kept at the source or at the corporate offices in Marshall, MN.	40 CFR Section 60.7(f); Minn. R. 7017.1130
CEMS Relative Accuracy Test Audit (RATA): due before end of each year following CEM Certification Test. If the relative accuracy is 15% or less the next CEMS RATA is not due for 24 months. Follow the procedures in 40 CFR pt. 60, Appendix F.	Minn. R. 7017.1170, subp. 5
Relative Accuracy Test Audit (RATA) Notification: due 30 days before CEMS Relative Accuracy Test Audit (RATA)	Minn. R. 7017.1180, subp. 2
Relative Accuracy Test Audit (RATA) Results Summary: due 30 days after end of each calendar quarter following CEMS Relative Accuracy Test Audit (RATA)	Minn. R. 7017.1180, subp. 3
Cylinder Gas Audit: due before end of each calendar half-year following CEM Certification Test. Conduct CGA at least 3 months apart and not greater than 8 months apart. If a RATA is performed during the calendar half-year, then the CGA is not required. Follow the procedures in 40 CFR 60, Appendix F.	Minn. R. 7017.1170, subp. 4
Cylinder Gas Audit (CGA) Results Summary: due 30 days after end of each calendar quarter following Cylinder Gas Audit.	Minn. R. 7017.1180, subp. 1

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: **SV 017 Fly Ash Bin**

Associated Items: EU 051 Fly Ash Bin

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.03 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.03 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.019 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE036) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
C. EMISSION UNIT OPERATION (EU051) - N/A	hdr
D. CONTROL EQUIPMENT OPERATION (CE036 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control required to meet modeling limit)
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 018 Bottom Ash Bin

Associated Items: EU 052 Bottom Ash Bin

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.03 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.03 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.019 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE037) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
C. EMISSION UNIT OPERATION (EU052) - N/A	hdr
D. CONTROL EQUIPMENT OPERATION (CE037 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control required to meet modeling limit)
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 019 Boiler #3

Associated Items: EU 053 Boiler #3

MR 003 NOx Monitor (Boiler #3)

MR 004 O2 Monitor (Boiler #3)

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.0095 lbs/million Btu heat input using 24-hour Block Average (1.7 lb/hr)	Title I Condition: To avoid classification of a previous modification as major under 40 CFR Section 52.21
Particulate Matter < 10 micron: less than or equal to 0.0095 lbs/million Btu heat input using 24-hour Block Average	Title I Condition: To avoid classification of a previous modification as major under 40 CFR Section 52.21
Particulate Matter < 10 micron: less than or equal to 1.7 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Sulfur Dioxide: less than or equal to 0.3 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Nitrogen Oxides: less than or equal to 0.125 lbs/million Btu heat input using an annual average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Nitrogen Oxides: less than or equal to 22.31 lbs/hour using an annual average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Nitrogen Oxides: less than or equal to 0.1 lbs/million Btu heat input using 30-day Rolling Average calculated using the 1-hour average emission rates measured by the continuous nitrogen oxides monitor. This limit applies at all times including periods of startup, shutdown, or malfunction.	40 CFR Section 60.44b(a)(1)(i); 40 CFR Section 60.44b(h) & (j); 40 CFR Section 60.46b(a); 40 CFR Section 60.48b(d); Minn. R. 7011.0565
Carbon Monoxide: less than or equal to 28.53 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
The Permittee must calibrate, maintain, and operate a continuous monitoring system for measuring nitrogen oxide emissions discharged to the atmosphere, and record the output of the system.	40 CFR Section 60.48b(b); Minn. R. 7011.0565; Minn. R. 7017.1006
30-day Performance Test to measure NOx emissions, upon request.	40 CFR Section 60.46b(e)(4); Minn. R. 7011.0565
C. EMISSION UNIT OPERATION and REPORTING (EU053)	hdr
Fuel Use: Limited to natural gas only	Title I Condition: 40 CFR Section 52.21(j) (BACT)
Recordkeeping: Each operating day, record the quantity of natural gas combusted and all of the information listed in 40 CFR 60.49b(g).	40 CFR Section 60.49b(d); 40 CFR Section 60.49b(g); Minn. R. 7011.0565
Records of Startup, Shutdown, or Malfunction: The owner or operator shall maintain records of the occurrence and duration of any startup, shutdown, or malfunction in the operation of the boiler; any malfunction of the air pollution control equipment; or any periods during which a continuous monitoring system or monitoring device is inoperative.	40 CFR Section 60.7(b)
D. CONTROL EQUIPMENT OPERATION	hdr
Burner requirements: Low-NOx burners	Title I Condition: 40 CFR Section 52.21(j) (BACT)
E. MONITOR OPERATING REQUIREMENTS (MR003)	hdr
The nitrogen oxide continuous monitoring system (CEMS) shall be operated and data recorded during all periods of operation of the boiler including startup, shutdown and malfunction, except for periods of acceptable monitor downtime. This requirement applies whether or not a numerical emission limit applies during these periods. A CEMS must not be bypassed except in emergencies where failure to bypass would endanger human health, safety, or plant equipment. Acceptable monitor downtime includes reasonable periods as listed in Items A, B, C and D of Minn. R. 7017.1090, subp. 2.	40 CFR Section 60.48b(c); 40 CFR Section 60.13(e)(6); Minn. R. 7011.0565; Minn. R. 7017.1090, subp. 1
The 1-hour average nitrogen oxides emission rates measured shall be expressed in units of lb/million Btu heat input and shall be used to calculate the average emission rates required under 40 CFR Section 60.44b.	40 CFR Section 60.48b(d); Minn. R. 7011.0565
Span Value: 500 ppm	40 CFR Section 60.48b(e)(2); Minn. R. 7011.0565
QA Plan: Develop and implement a written quality assurance plan that covers each CEMS. The plan shall be on site and available for inspection 30 days after monitor certification. The plan shall contain all of the information required by 40 CFR Section 60, Appendix F, section 3.	40 CFR pt. 60, Appendix F, section 3; Minn. R. 7017.1170, subp. 2

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

CEMS Daily Calibration Drift (CD) Test: The CD shall be quantified and recorded at zero (low level value between 0 and 20 percent of span value) and span (50 to 100 percent of span value) gas concentrations at least once daily. The CEMS shall be adjusted whenever the CD exceeds twice the specification of 40 CFR 60, Appendix B. 40 CFR 60, Appendix F, shall be used to determine out-of-control periods for CEMS.	40 CFR Section 60, Appendix F, section 4.1; 40 CFR Section 60.13(d)(1); Minn. R. 7017.1170, subp. 3
Recordkeeping: The owner or operator must retain records of all CEMS monitoring data and support information for a period of five years from the date of the monitoring sample, measurement, or report. Records shall be kept at the source or at the corporate office in Marshall, MN.	40 CFR Section 60.7(f); Minn. R. 7017.1130
CEMS Relative Accuracy Test Audit (RATA): due before end of each year following CEM Certification Test. Follow the procedures in 40 CFR pt. 60, Appendix F.	40 CFR pt. 60, Appendix F, section 5.1.1; Minn. R. 7017.1170, subp. 5
Relative Accuracy Test Audit (RATA) Notification: due 30 days before CEMS Relative Accuracy Test Audit (RATA).	Minn. R. 7017.1180, subp. 2
Relative Accuracy Test Audit (RATA) Results Summary: due 30 days after end of each calendar quarter following CEMS Relative Accuracy Test Audit (RATA).	Minn. R. 7017.1180, subp. 3; 40 CFR Section 60, Subpart Db; 40 CFR Section 60, Appendix F, Section 1
Cylinder Gas Audit: due before end of each calendar quarter following CEM Certification Test but in no more than three calendar quarters per calendar year. The RATA shall be conducted during the calendar quarter in which a CGA is not performed.	40 CFR Section 60, Appendix F, section 5.1.2; Minn. R. 7017.1170, subp. 4
Cylinder Gas Audit (CGA) Results Summary: due 30 days after end of each calendar quarter following Cylinder Gas Audit.	40 CFR 60, Subpart Db; 40 CFR 60, Appendix F, section1; Minn. R. 7017.1180, subp. 1

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 020 Boiler #4

Associated Items: EU 054 Boiler #4

MR 005 NOx Monitor (Boiler #4)

MR 006 O2 Monitor (Boiler #4)

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.0084 lbs/million Btu heat input using 24-hour Block Average (2.0 lb/hr)	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Particulate Matter < 10 micron: less than or equal to 0.0084 lbs/million Btu heat input using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Particulate Matter < 10 micron: less than or equal to 2.0 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Sulfur Dioxide: less than or equal to 0.4 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Nitrogen Oxides: less than or equal to 24.1 lbs/hour using an annual average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Nitrogen Oxides: less than or equal to 0.1 lbs/million Btu heat input using 30-day Rolling Average calculated using the 1-hour average emission rates measured by the continuous nitrogen oxides monitor. This limit applies at all times including periods of startup, shutdown, or malfunction.	40 CFR Section 60.44b(a)(1)(i); 40 CFR Section 60.44b(h) & (i); 40 CFR Section 60.46b(a); 40 CFR Section 60.48b(d); Minn. R. 7011.0565
Carbon Monoxide: less than or equal to 38.56 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each 36 months starting 12/05/2003 to measure PM10 emissions. The first test is due December 5, 2003, then every 36 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	Title I Condition: Testing for 40 CFR Section 52.21(j) limits and Minn. R. 7017.2020, subp. 1
Performance Test: due before end of each 60 months starting 01/31/2003 to measure total particulate matter, NOx, and CO emissions. The tests shall be conducted at an interval not to exceed 60 months between test dates. The first test is due on or before January 31, 2003, then every 60 months, thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	Title I Condition: Testing for 40 CFR Section 52.21(j) limit and Minn. R. 7017.2020, subp. 1
30-day Performance Test to measure NOx emissions, upon request.	40 CFR Section 60.46b(e)(4); Minn. R. 7011.0565
The Permittee must calibrate, maintain, and operate a continuous monitoring system for measuring nitrogen oxide emissions discharged to the atmosphere, and record the output of the system.	40 CFR Section 60.48b(b); Minn. R. 7011.0565; Minn. R. 7017.1006
C. EMISSION UNIT OPERATION and REPORTING (EU054)	hdr
Steam Flow: less than or equal to 221400 lbs/hour using 24-hour Block Average of steam. Downtime of 15 minutes or more is not to be counted as operating time.	Minn. R. 7017.2025
Recordkeeping of Steam Flow: Each day, calculate the total steam flow for the previous day, in pounds per day. Divide the total steam flow for the day by the hours of operating time. Do not count downtime of 15 minutes or more as operating time.	Minn. R. 7007.0800, subp. 5
Fuel Use: Limited to natural gas only	Title I Condition: 40 CFR Section 52.21(j) (BACT for PM, PM10, and SO2)
Recordkeeping: Each operating day, record the quantity of natural gas combusted and all of the information listed in 40 CFR 60.49b(g).	40 CFR Section 60.49b(d); 40 CFR Section 60.49b(g); Minn. R. 7011.0565
Records of Startup, Shutdown, or Malfunction: The owner or operator shall maintain records of the occurrence and duration of any startup, shutdown, or malfunction in the operation of the boiler; any malfunction of the air pollution control equipment; or any periods during which a continuous monitoring system or monitoring device is inoperative.	40 CFR Section 60.7(b)
D. CONTROL EQUIPMENT OPERATION	hdr
Burner requirements: Low-NOx multistage combustion with induced flue gas recirculation	Title I Condition: 40 CFR Section 52.21(j) (BACT for CO and NOx)
E. MONITOR OPERATING REQUIREMENTS (MR005)	hdr

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

<p>The nitrogen oxide continuous monitoring system (CEMS) shall be operated and data recorded during all periods of operation of the boiler including startup, shutdown and malfunction, except for periods of acceptable monitor downtime. This requirement applies whether or not a numerical emission limit applies during these periods. A CEMS must not be bypassed except in emergencies where failure to bypass would endanger human health, safety, or plant equipment.</p> <p>Acceptable monitor downtime includes reasonable periods as listed in Items A, B, C and D of Minn. R. 7017.1090, subp. 2.</p>	<p>40 CFR Section 60.48b(c); 40 CFR Section 60.13(e)(6); Minn. R. 7011.0565; Minn. R. 7017.1090, subp. 1</p>
<p>The 1-hour average nitrogen oxides emission rates measured shall be expressed in units of lb/million Btu heat input and shall be used to calculate the average emission rates required under 40 CFR Section 60.44b.</p>	<p>40 CFR Section 60.48b(d); Minn. R. 7011.0565</p>
<p>Span Value: 500 ppm</p>	<p>40 CFR Section 60.48b(e)(2); Minn. R. 7011.0565</p>
<p>QA Plan: Develop and implement a written quality assurance plan that covers each CEMS. The plan shall be on site and available for inspection 30 days after monitor certification. The plan shall contain all of the information required by 40 CFR Section 60, Appendix F, section 3.</p>	<p>40 CFR pt. 60, Appendix F, section 3; Minn. R. 7017.1170, subp. 2</p>
<p>CEMS Daily Calibration Drift (CD) Test: The CD shall be quantified and recorded at zero (low level value between 0 and 20 percent of span value) and span (50 to 100 percent of span value) gas concentrations at least once daily. The CEMS shall be adjusted whenever the CD exceeds twice the specification of 40 CFR 60, Appendix B. 40 CFR 60, Appendix F, shall be used to determine out-of-control periods for CEMS.</p>	<p>40 CFR Section 60, Appendix F, section 4.1; 40 CFR Section 60.13(d)(1); Minn. R. 7017.1170, subp. 3</p>
<p>Recordkeeping: The owner or operator must retain records of all CEMS monitoring data and support information for a period of five years from the date of the monitoring sample, measurement, or report. Records shall be kept at the source or at the corporate offices in Marshall, MN.</p>	<p>40 CFR Section 60.7(f); Minn. R. 7017.1130</p>
<p>CEMS Relative Accuracy Test Audit (RATA): due before end of each year following CEM Certification Test. Follow the procedures in 40 CFR pt. 60, Appendix F.</p>	<p>40 CFR pt. 60, Appendix F, section 5.1.1; Minn. R. 7017.1170, subp. 5</p>
<p>Relative Accuracy Test Audit (RATA) Notification: due 30 days before CEMS Relative Accuracy Test Audit (RATA)</p>	<p>Minn. R. 7017.1180, subp. 2</p>
<p>Relative Accuracy Test Audit (RATA) Results Summary: due 30 days after end of each calendar quarter following CEMS Relative Accuracy Test Audit (RATA)</p>	<p>Minn. R. 7017.1180, subp. 3; 40 CFR Section 60, Subpart Db; 40 CFR Section 60, Appendix F, Section 1</p>
<p>Cylinder Gas Audit: due before end of each calendar quarter following CEM Certification Test but in no more than three calendar quarters per calendar year. The RATA shall be conducted during the calendar quarter in which a CGA is not performed.</p>	<p>40 CFR Section 60, Appendix F, section 5.1.2; Minn. R. 7017.1170, subp. 4</p>
<p>Cylinder Gas Audit (CGA) Results Summary: due 30 days after end of each calendar quarter following Cylinder Gas Audit.</p>	<p>40 CFR 60, Subpart Db; 40 CFR 60, Appendix F, section1; Minn. R. 7017.1180, subp. 1</p>

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 021 Generator

Associated Items: EU 055 Generator

What to do	Why to do it
A. EMISSION LIMITS	hdr
Opacity: less than or equal to 20 percent opacity once operating temperatures have been attained	Minn. R. 7011.2300, subp. 1
Sulfur Dioxide: less than or equal to 0.5 lbs/million Btu heat input	Minn. R. 7011.2300, subp. 2
B. EMISSION TESTING AND MONITORING REQUIREMENTS -- N/A	hdr
C. EMISSION UNIT OPERATION (EU055)	hdr
May only be used in times of total or partial power loss, or for routine testing. May not be a regular power source for routine plant operation.	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Recordkeeping: Record the date and times that the generator is operated.	Title I Condition: Recordkeeping for 40 CFR Section 52.21(k); Minn. R. 7007.3000
D. CONTROL EQUIPMENT OPERATION -- N/A	hdr

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 022 Wastewater Treatment Plant Flare

Associated Items: EU 056 Anaerobic Reactor #1

EU 062 Anaerobic Reactor #2

What to do	Why to do it
A. EMISSION LIMITS	hdr
Sulfur Dioxide: less than or equal to 0.29 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Nitrogen Oxides: less than or equal to 0.55 lbs/hour using an annual average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Carbon Monoxide: less than or equal to 2.96 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS -- N/A	hdr
C. EMISSION UNIT OPERATION (EU056 & EU062) -- N/A	hdr
D. CONTROL EQUIPMENT OPERATION (CE038 - flare)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control required to meet modeling limit)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 023 Product Transfer

Associated Items: EU 029 Transfer operation

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 1.71 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 1.71 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.005 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of EU029) for any visible emissions two (2) times per calendar week, when the unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Performance Test: due before end of each 60 months starting 09/26/2005 to measure total particulate matter emissions at the stack. The first test is due September 26, 2005, then every 60 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1)Title I Condition: Testing for 40 CFR Section 52.21(j) limit; (2)Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits; (1&2) Minn. R. 7017.2020, subp. 1
Performance Test: due before end of each 36 months starting 09/26/2003 to measure PM10 emissions from the stack. The first test is due September 26, 2003, then every 36 months thereafter. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	(1)Title I Condition: Testing for 40 CFR Section 52.21(j) limit; (2)Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits; (1&2) Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU029)	hdr
Process Throughput: less than or equal to 26749 lbs/hour using 30-day Rolling Average of product. Downtime of 15 minutes or more is not to be counted as operating time.	Minn. R. 7017.2025
Recordkeeping of Throughput: Each day, calculate the amount of product transferred for the previous day and for the previous 30-day period. Divide the total amount of product transferred for the previous 30-day period by the hours of operating time during the previous 30-day period. Do not count downtime of 15 minutes or more as operating time.	Minn. R. 7007.0800, subp. 5
Recordkeeping of Visible Emissions: The Permittee shall record the time and date of each visible emission inspection and whether or not any visible emissions were observed.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Corrective Actions: If visible emissions are observed, the Permittee shall begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
D. CONTROL EQUIPMENT OPERATION - N/A	hdr

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 024 Corn Silos #7-#11

Associated Items: EU 057 Corn Receiving Silo #7

EU 058 Corn Receiving Silo #8

EU 059 Corn Receiving Silo #9

EU 066 Corn Receiving Silo #10

EU 067 Corn Receiving Silo #11

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.18 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Particulate Matter < 10 micron: less than or equal to 0.18 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.011 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 10 percent opacity	Minn. R. 7011.1005, subp. 3(D)
Opacity: less than or equal to 5 percent opacity from fugitive emissions (emissions directly from the unit, not collected by ductwork to the fabric filter)	Minn. R. 7011.1005, subp. 3(A)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE061) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(j)
C. EMISSION UNIT OPERATION (EU057 - EU059, EU066, EU067)	hdr
The Permittee shall clean up commodities spilled on the driveway and other facility property as required to minimize fugitive emissions to a level consistent with RACT (reasonably available control technology).	Minn. R. 7011.1005, subp. 1(A)
D. CONTROL EQUIPMENT OPERATION (CE061 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(j) (BACT)
Total Particulate Matter: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) [Also meets the requirements of Minn. R. 7011.1005, subp. 3(E)]
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(j) & (k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 029 Corn Fines Transfer

Associated Items: EU 068 Corn Fines Transfer

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.14 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit)
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.14 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(j) (BACT limit); 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.009 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of EU068) for any visible emissions two (2) times per calendar week, when the unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(j) & (k)
Performance Test: due before end of each 60 months starting 09/26/2005 to measure (1) total particulate matter and (2) PM10 emissions at the stack. The first test is due September 26, 2005, then every 60 months thereafter.	(1) Title I Condition: Testing for 40 CFR Section 52.21(j) limit; (2) Title I Condition: Testing for 40 CFR Section 52.21(j) and (k) limits; (1&2) Minn. R. 7017.2020, subp. 1
For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	
C. EMISSION UNIT OPERATION (EU068)	hdr
Process Throughput: less than or equal to 48950 bushel/hour using 24-hour Block Average of corn fines. Downtime of 15 minutes or more is not to be counted as operating time.	Minn. R. 7017.2025
Recordkeeping of Throughput: Each day, calculate the amount of corn fines processed for the previous day, in bushels per hour. Divide the total amount of corn fines by the hours of operating time. Do not count downtime of 15 minutes or more as operating time.	Minn. R. 707.0800, subp. 5
Recordkeeping of Visible Emissions: The Permittee shall record the time and date of each visible emission inspection and whether or not any visible emissions were observed.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Corrective Actions: If visible emissions are observed, the Permittee shall begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
D. CONTROL EQUIPMENT OPERATION - N/A	hdr

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 030 Rotary Cooler

- Associated Items:** EU 023 Rotary Cooler
 EU 119 Dryer #2 Baghouse
 EU 120 Dryer #3 Baghouse
 EU 121 Dryer #4 Baghouse
 EU 122 Dryers #5 & #6 Baghouse

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 3.57 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 3.57 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.011 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, two (2) times per calendar week, when the emission units are in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Performance Test: due before end of each calendar 60 months starting 06/27/2001 to measure total particulate matter emissions. For additional applicable performance testing requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	Minn. R. 7009.0200 (Testing for permit limit) and Minn. R. 7017.2020, subp. 1
Performance Test: due before end of each calendar 60 months starting 06/27/2001 to measure PM10 emissions. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	Title I Condition: Testing for 40 CFR Section 52.21(k) limit and Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU023, EU119, EU120, EU121, EU122)	hdr
Recordkeeping of Visible Emissions: The Permittee shall record the time and date of each visible emission inspection and whether or not any visible emissions were observed.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Corrective Actions: If visible emissions are observed, the Permittee shall begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
D. CONTROL EQUIPMENT OPERATION (CE016 - Fabric Filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control equipment required to meet modeling limits)
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21 (k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 8.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(j) & (k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 033 Fiber Dewatering & Chemical Storage

Associated Items: EU 107 Chemical Storage/Fiber Dewatering System

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.6 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.6 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.007 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
Sulfur Dioxide: less than or equal to 0.49 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Performance Test: due before end of each calendar 60 months starting 06/26/2001 to measure total particulate matter emissions For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	Minn. R. 7007.0200 (Testing for permit limit) and Minn. R. 7017.2020, subp. 1
Performance Test: due before end of each calendar 60 months starting 06/26/2001 to measure PM10 and SO2 emissions. For additional applicable performance test requirements, see "General Performance Test Requirements" in Table A, Subject Item "Total Facility".	Title I Condition: Testing for 40 CFR Section 52.21(k) limit and Minn. R. 7017.2020, subp. 1
C. EMISSION UNIT OPERATION (EU107) -- N/A	hdr
D. CONTROL EQUIPMENT OPERATION (CE069 - packed gas absorption column)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control required to meet modeling limit)
Particulate Matter < 10 micron: greater than or equal to 90 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Sulfur Dioxide: greater than or equal to 70 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 4.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Water flow rate: greater than or equal to 100 gallons/minute and less than or equal to 200 gallons/minute	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
pH of scrubber water: greater than or equal to 6.0 and less than or equal to 8.0	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Pressure Drop: Once each operating day, read and record pressure drop.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Water Flow Rate: Once each operating day, read and record the water flow rate.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of pH: Once each operating day, read and record the pH.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Corrective Actions: If the recorded pressure drop, water flow rate, or pH is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for CE069 and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 034 Loadout Building

- Associated Items:** EU 010 Bin #1
 EU 011 Bin #2
 EU 012 Bin #3
 EU 013 Bin #4
 EU 024 Bin #5
 EU 025 Bin #6
 EU 026 Bin #7
 EU 027 Bin #10
 EU 030 Bin #8
 EU 031 Bin #9

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.21 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.21 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.018 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the roof vent (SV034) for any visible emissions, or, during inclement weather, read and record the pressure drop across each of the baghouses, two (2) times per calendar week, when the emission units are in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
C. EMISSION UNIT OPERATION (EU010 - EU013, EU024 - EU027, EU030, EU031) - N/A	hdr
D. CONTROL EQUIPMENT OPERATION (CE007 - CE010, CE017 - CE020, CE023, CE024 - fabric filters)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control equipment required to meet modeling limits)
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 10.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 035 Storage Silo

Associated Items: EU 061 Lime Storage Tank

EU 109 Storage Silo

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.08 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.08 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.010 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE071) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
C. EMISSION UNIT OPERATION (EU061& EU109) -- N/A	hdr
D. CONTROL EQUIPMENT OPERATION (CE071 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control equipment required to meet modeling limits)
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 4.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 036 Lime Storage Silo

Associated Items: EU 110 Lime Storage Silo

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.13 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.13 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.010 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE072) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
C. EMISSION UNIT OPERATION (EU110) -- N/A	hdr
D. CONTROL EQUIPMENT OPERATION (CE072 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control equipment required to meet modeling limits)
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 5.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 037 Soda Ash Storage Silo

Associated Items: EU 111 Soda Ash Storage Silo

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.13 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.13 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000)
Particulate Matter < 10 micron: less than or equal to 0.010 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE073) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse, two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
D. EMISSION UNIT OPERATION (EU111) -- N/A	hdr
E. CONTROL EQUIPMENT OPERATION (CE073 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control equipment required to meet modeling limits)
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 5.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 038 WWTP Package Boiler

Associated Items: EU 113 WWTP Package Boiler

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.01 lbs/hour using 24-hour Block Average (0.015 lbs/ million Btu heat input) This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.4 lbs/million Btu heat input	Minn. R. 7011.0515, subp. 1
Particulate Matter < 10 micron: less than or equal to 0.01 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.015 lbs/million Btu heat input	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity , except for one six-minute period per hour of not more than 60 percent opacity. (An exceedance of this opacity standard occurs whenever any one-hour period contains two or more six-minute periods during which the average opacity exceeds 20 percent or whenever any one-hour period contains one or more six-minute periods during which the average opacity exceeds 60 percent.)	Minn. R. 7011.0515, subp. 2
Sulfur Dioxide: less than or equal to 0.01 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Nitrogen Oxides: less than or equal to 0.1 lbs/hour using an annual average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Carbon Monoxide: less than or equal to 0.04 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS -- N/A	hdr
C. EMISSION UNIT OPERATION (EU113)	hdr
Fuel Use: Limited to natural gas only, by equipment design	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
D. CONTROL EQUIPMENT OPERATION -- N/A	hdr

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 039 Natural Gas Heater

Associated Items: EU 114 Natural Gas Heater

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.01 lbs/hour using 24-hour Block Average (0.005 lbs/ million Btu heat input) This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.01 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.005 lbs/million Btu heat input using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
Sulfur Dioxide: less than or equal to 0.01 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Nitrogen Oxides: less than or equal to 0.2 lbs/hour using an annual average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Carbon Monoxide: less than or equal to 0.13 lbs/hour using 1-Hour Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
B. EMISSION TESTING AND MONITORING REQUIREMENTS -- N/A	hdr
C. EMISSION UNIT OPERATION (EU114)	hdr
Fuel Use: Limited to natural gas only, by equipment design	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
D. CONTROL EQUIPMENT OPERATION -- N/A	hdr

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: SV 041 Soda Ash Blending

Associated Items: EU 116 Soda Ash Blending

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.04 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.04 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.008 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of EU116) for any visible emissions, or, during inclement weather, read and record the pressure drop across the unit, two (2) times per calendar week, when the unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
C. EMISSION UNIT OPERATION (EU116)	hdr
Operation and Maintenance of Fabric Filter: The Permittee shall conduct all necessary maintenance and make all necessary attempts to keep the unit in proper operating condition at all times. The Permittee shall operate and maintain the unit according to the equipment manufacturer's specifications or the Operation and Maintenance Plan developed by the Permittee.	Title I Condition: Monitoring for 40 CFR Section 52.21(j)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 5.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit
The Permittee shall inspect the unit according to manufacturer's specifications or an Operation and Maintenance Plan developed by the Permittee and maintain a written record of the inspection and any action resulting from the inspection.	Minn. R. 7007.0800, subp. 2 and subp. 14
D. CONTROL EQUIPMENT OPERATION - N/A	hdr

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: **SV 043 Soda Ash Bin**

Associated Items: EU 118 Soda Ash Bin

What to do	Why to do it
A. EMISSION LIMITS	hdr
Total Particulate Matter: less than or equal to 0.1 lbs/hour using 24-hour Block Average This is a state only requirement and is not enforceable under the Clean Air Act by the EPA Administrator or by the citizens.	Minn. R. 7009.0200
Total Particulate Matter: less than or equal to 0.3 grains/dry standard cubic foot of exhaust gas from control equipment, or the allowable concentration at the actual flow rate, as described in Minn. R. 7011.0735, or the allowable emission rate at the actual process weight rate, as described in Minn. R. 7011.0730.	Minn. R. 7011.0715, subp. 1(A)
Particulate Matter < 10 micron: less than or equal to 0.1 lbs/hour using 24-hour Block Average	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Particulate Matter < 10 micron: less than or equal to 0.009 grains/actual cubic foot	Title I Condition: 40 CFR Section 52.21(k); Minn. R. 7007.3000
Opacity: less than or equal to 20 percent opacity	Minn. R. 7011.0715, subp. 1(B)
B. EMISSION TESTING AND MONITORING REQUIREMENTS	hdr
Visible Emissions: The Permittee shall check the stack (outlet of CE077) for any visible emissions, or, during inclement weather, read and record the pressure drop across the baghouse two (2) times per calendar week, when the emission unit is in operation.	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
C. EMISSION UNIT OPERATION (EU118) -- N/A	hdr
D. CONTROL EQUIPMENT OPERATION (CE077 - fabric filter)	hdr
Control equipment shall be operated at all times that the associated emission units are in operation.	Title I Condition: 40 CFR Section 52.21(k) (use of control required to meet modeling limit)
Particulate Matter < 10 micron: greater than or equal to 99 percent control efficiency	Title I Condition: Control required for 40 CFR Section 52.21(k)
Pressure Drop: greater than or equal to 0.1 inches of water column and less than or equal to 5.0 inches of water column	Title I Condition: Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Visible Emissions or Pressure Drop: The Permittee shall record the time and date of each visible emission inspection or pressure drop reading, and whether or not any visible emissions were observed, or whether or not the observed pressure drop was within the range specified herein.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit
Recordkeeping of Corrective Actions: If visible emissions are observed, or if the recorded pressure drop is outside the required operating range, the Permittee shall follow the Operation and Maintenance Plan for the fabric filter and begin corrective actions as soon as possible (within 24 hours) to correct the problem. The Permittee shall keep a record of the corrective actions taken.	Title I Condition: Recordkeeping of Monitoring for 40 CFR Section 52.21(k) limit

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: TK 001 Ethanol (1080TK01)

What to do	Why to do it
Recordkeeping: Maintain records showing the dimensions of the tank and an analysis showing the tank capacity. These records shall be maintained for the life of the source.	40 CFR Section 60.116b(b); Minn. R. 7011.1520(C)
Recordkeeping: Maintain records showing the volatile organic liquid (VOL) stored, the period of storage, and the maximum true vapor pressure of the VOL during the respective storage period, calculated as described in 40 CFR Section 116b(e).	40 CFR Section 60.116b(c); Minn. R. 7011.1520(C)
Notification: Within 30 days of each occurrence, notify the Commissioner when the maximum true vapor pressure exceeds 5.2 kPa.	40 CFR Section 60.116b(d); Minn. R. 7011.1520(C)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: TK 002 Ethanol (1080TK02)

What to do	Why to do it
Recordkeeping: Maintain records showing the dimensions of the tank and an analysis showing the tank capacity. These records shall be maintained for the life of the source.	40 CFR Section 60.116b(b); Minn. R. 7011.1520(C)
Recordkeeping: Maintain records showing the volatile organic liquid (VOL) stored, the period of storage, and the maximum true vapor pressure of the VOL during the respective storage period, calculated as described in 40 CFR Section 116b(e).	40 CFR Section 60.116b(c); Minn. R. 7011.1520(C)
Notification: Within 30 days of each occurrence, notify the Commissioner when the maximum true vapor pressure exceeds 5.2 kPa.	40 CFR Section 60.116b(d); Minn. R. 7011.1520(C)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: TK 003 Denaturant (gasoline) (1080TK04)

What to do	Why to do it
A. POLLUTION CONTROL REQUIREMENTS	hdr
The storage vessel shall be equipped with a fixed roof in combination with an internal floating roof meeting the specifications of paragraph (a)(1) of this section.	40 CFR Section 60.112b(a); Minn. R. 7011.1520(C)
The internal floating roof shall be equipped with the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: (B) Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.	40 CFR Section 60.112b(a)(1)(ii)(B); Minn. R. 7011.1520(C)
B. MONITORING REQUIREMENTS	hdr
Visually inspect the internal floating roof, the primary seal, and the secondary seal through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill as required by this paragraph.	40 CFR Section 60.113b(a)(3)(ii); Minn. R. 7011.1520(C)
Visually inspect the internal floating roof, the primary seal, the secondary seal, gaskets, slotted membranes, and sleeve seals (if any) each time the storage vessel is emptied and degassed as required by this paragraph. In no event shall inspections conducted in accordance with this provision occur at intervals greater than five (5) years.	40 CFR Section 60.113b(a)(3)(i); Minn. R. 7011.1520(C)
C. RECORDKEEPING REQUIREMENTS	hdr
Recordkeeping: Maintain records showing the dimensions of the tank and an analysis showing the tank capacity. These records shall be maintained for the life of the source.	40 CFR Section 60.116b(b); Minn. R. 7011.1520(C)
Keep a record of each inspection performed as required by 40 CFR Section 60.113b(a)(1), (a)(2), (a)(3), and (a)(4). Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).	40 CFR Section 60.115b(a)(2); Minn. R. 7011.1520(C)
D. REPORTING REQUIREMENTS	hdr
After each inspection required by 40 CFR Section 60.113b(a)(3) that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in 40 CFR Section 60.113b(a)(3)(ii), a report shall be furnished to the Administrator within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of 40 CFR Section 60.112b(a)(1) or 40 CFR Section 60.113b(a)(3)(ii) and list each repair made.	40 CFR Section 60.115b(a)(4); Minn. R. 7011.1520(C)
Notification: If an inspection is required (under 40 CFR Section 60.113b(a)(1) or 40 CFR Section 60.113b(a)(3)(i)), notify the Administrator in writing at least 30 days prior to filling or refilling of the storage vessel, to afford the Administrator the opportunity to have an observer present. If the inspection is not planned and the owner or operator could not have known about the inspection 30 days in advance of refilling the tank, the owner or operator shall notify the Administrator at least 7 days prior to refilling the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Administrator at least 7 days prior to refilling.	40 CFR Section 60.115b(a)(5); Minn. R. 7011.1520(C)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: TK 005 Ethanol (1080TK03)

What to do	Why to do it
Recordkeeping: Maintain records showing the dimensions of the tank and an analysis showing the tank capacity. These records shall be maintained for the life of the source.	40 CFR Section 60.116b(b); Minn. R. 7011.1520(C)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: TK 006 Ethanol (1080TK06)

What to do	Why to do it
Recordkeeping: Maintain records showing the dimensions of the tank and an analysis showing the tank capacity. These records shall be maintained for the life of the source.	40 CFR Section 60.116b(b); Minn. R. 7011.1520(C)
Recordkeeping: Maintain records showing the volatile organic liquid (VOL) stored, the period of storage, and the maximum true vapor pressure of the VOL during the respective storage period, calculated as described in 40 CFR Section 116b(e).	40 CFR Section 60.116b(c); Minn. R. 7011.1520(C)
Notification: Within 30 days of each occurrence, notify the Commissioner when the maximum true vapor pressure exceeds 5.2 kPa.	40 CFR Section 60.116b(d); Minn. R. 7011.1520(C)

TABLE A: LIMITS AND OTHER REQUIREMENTS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Subject Item: TK 015 Denatured Ethanol (1080TK07)

What to do	Why to do it
A. POLLUTION CONTROL REQUIREMENTS	hdr
The storage vessel shall be equipped with a fixed roof in combination with an internal floating roof meeting the specifications of paragraph (a)(1) of this section.	40 CFR Section 60.112b(a); Minn. R. 7011.1520(C)
The internal floating roof shall be equipped with the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: (B) Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.	40 CFR Section 60.112b(a)(1)(ii)(B); Minn. R. 7011.1520(C)
B. MONITORING REQUIREMENTS	hdr
Visually inspect the internal floating roof, the primary seal, and the secondary seal through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill as required by this paragraph.	40 CFR Section 60.113b(a)(3)(ii); Minn. R. 7011.1520(C)
Visually inspect the internal floating roof, the primary seal, the secondary seal, gaskets, slotted membranes, and sleeve seals (if any) each time the storage vessel is emptied and degassed as required by this paragraph. In no event shall inspections conducted in accordance with this provision occur at intervals greater than five (5) years.	40 CFR Section 60.113b(a)(3)(i); Minn. R. 7011.1520(C)
C. RECORDKEEPING REQUIREMENTS	hdr
Recordkeeping: Maintain records showing the dimensions of the tank and an analysis showing the tank capacity. These records shall be maintained for the life of the source.	40 CFR Section 60.116b(b); Minn. R. 7011.1520(C)
Keep a record of each inspection performed as required by 40 CFR Section 60.113b(a)(1), (a)(2), (a)(3), and (a)(4). Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).	40 CFR Section 60.115b(a)(2); Minn. R. 7011.1520(C)
D. REPORTING REQUIREMENTS	hdr
After each inspection required by 40 CFR Section 60.113b(a)(3) that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in 40 CFR Section 60.113b(a)(3)(ii), a report shall be furnished to the Administrator within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of 40 CFR Section 60.112b(a)(1) or 40 CFR Section 60.113b(a)(3)(ii) and list each repair made.	40 CFR Section 60.115b(a)(4); Minn. R. 7011.1520(C)
Notification: If an inspection is required (under 40 CFR Section 60.113b(a)(1) or 40 CFR Section 60.113b(a)(3)(i)), notify the Administrator in writing at least 30 days prior to filling or refilling of the storage vessel, to afford the Administrator the opportunity to have an observer present. If the inspection is not planned and the owner or operator could not have known about the inspection 30 days in advance of refilling the tank, the owner or operator shall notify the Administrator at least 7 days prior to refilling the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Administrator at least 7 days prior to refilling.	40 CFR Section 60.115b(a)(5); Minn. R. 7011.1520(C)

TABLE B: SUBMITTALS

11/07/03

Facility Name: ADM Corn Processing - Marshall
Permit Number: 08300038 - 006

Table B lists most of the submittals required by this permit. Please note that some submittal requirements may appear in Table A or, if applicable, within a compliance schedule located in Table C. Table B is divided into two sections in order to separately list one-time only and recurrent submittal requirements.

Each submittal must be postmarked or received by the date specified in the applicable Table. Those submittals required by parts 7007.0100 to 7007.1850 must be certified by a responsible official, defined in Minn. R. 7007.0100, subp. 21. Other submittals shall be certified as appropriate if certification is required by an applicable rule or permit condition.

Send any application for a permit or permit amendment to:

Permit Technical Advisor
Permit Section
Air Quality Division
Minnesota Pollution Control Agency
520 Lafayette Road North
St. Paul, Minnesota 55155-4194

Also, where required by an applicable rule or permit condition, send to the Permit Technical Advisor notices of:

- accumulated insignificant activities,
- installation of control equipment,
- replacement of an emissions unit, and
- changes that contravene a permit term.

Unless another person is identified in the applicable Table, send all other submittals to:

Supervisor
Compliance Determination Unit
Air Quality Division
Minnesota Pollution Control Agency
520 Lafayette Road North
St. Paul, Minnesota 55155-4194

Send submittals that are required to be submitted to the U.S. EPA regional office to:

Mr. George Czerniak
Air and Radiation Branch
EPA Region V
77 West Jackson Boulevard
Chicago, Illinois 60604

Send submittals that are required by the Acid Rain Program to:

U.S. Environmental Protection Agency
Clean Air Markets Division
1200 Pennsylvania Avenue NW (6204N)
Washington, D.C. 20460

TABLE B: ONE TIME SUBMITTALS OR NOTIFICATIONS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

What to send	When to send	Portion of Facility Affected
Application for Permit Reissuance	due 180 days before expiration of Existing Permit Submit all permit applications to the Air Quality Permit Technical Advisor, Minnesota Pollution Control Agency, Metro District/Major Facilities, 520 Lafayette Road North, St. Paul, MN 55155	Total Facility
Testing Frequency Plan	due 60 days after Initial Performance Test for particulate matter and PM10. The plan shall specify a testing frequency based on test data and MPCA guidance. Future performance tests based on year (12-month), 36 month, or 60-month intervals, or as applicable, shall be required upon written approval of MPCA.	SV030
Testing Frequency Plan	due 60 days after Initial Performance Test for particulate matter, PM10, and SO2. The plan shall specify a testing frequency based on test data and MPCA guidance. Future performance tests based on year (12-month), 36 month, or 60-month intervals, or as applicable, shall be required upon written approval of MPCA.	SV033
Testing Frequency Plan	due 60 days after Initial Performance Test for sulfur dioxide. The plan shall specify a testing frequency based on test data and MPCA guidance. Future performance tests based on year (12-month), 36 month, or 60-month intervals, or as applicable, shall be required upon written approval of MPCA.	SV015

TABLE B: RECURRENT SUBMITTALS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

What to send	When to send	Portion of Facility Affected
Excess Emissions/Downtime Reports (EER's)	due 30 days after end of each calendar quarter starting 08/08/2000 (use Deviations Reporting Form DRF-1 as amended). The EER must contain all of the information requested in 40 CFR Section 60.7(c). The EER shall indicate all periods of monitor bypass and all periods of exceedances of the limit including exceedances allowed during startup, shutdown, and malfunction.	SV016
Excess Emissions/Downtime Reports (EER's)	due 30 days after end of each calendar quarter starting 08/08/2000 (use Deviations Reporting Form DRF-1 as amended). The EER must contain all of the information requested in 40 CFR Section 60.7(c). The EER shall indicate all periods of monitor bypass and all periods of exceedances of the limit including exceedances allowed during startup, shutdown, and malfunction.	SV019
Excess Emissions/Downtime Reports (EER's)	due 30 days after end of each calendar quarter starting 08/08/2000 (use Deviations Reporting Form DRF-1 as amended). The EER must contain all of the information requested in 40 CFR Section 60.7(c). The EER shall indicate all periods of monitor bypass and all periods of exceedances of the limit including exceedances allowed during startup, shutdown, and malfunction.	SV020
Quarterly Report	due 30 days after end of each calendar quarter starting 08/08/2000 . Report must contain all of the information listed in 40 CFR 60.49b(g).	SV020
Quarterly Report	due 30 days after end of each calendar quarter starting 08/16/2001 . Report must contain all of the information listed in 40 CFR 60.49b(g).	SV019
Semiannual Deviations Report	due 30 days after end of each calendar half-year starting 08/08/2000 . The first semiannual report submitted by the Permittee shall cover the calendar half-year in which the permit is issued. The first report of each calendar year covers January 1 - June 30. The second report of each calendar year covers July 1 - December 31. The report shall be sent to: Air Quality Compliance Tracking Coordinator, Minnesota Pollution Control Agency, 520 Lafayette Road North, St. Paul, MN 55155	Total Facility
Compliance Certification	<p>due 30 days after end of each calendar year starting 08/08/2000 (for the previous calendar year). To be submitted on a form approved by the Commissioner , both to the Commissioner, and to the U.S. EPA regional office in Chicago. This report covers all deviations experienced during the calendar year.</p> <p>The EPA copy shall be sent to: Mr. George Czerniak, Chief, Air Enforcement and Compliance Assurance Branch, Air and Radiation Division, EPA Region V, 77 West Jackson Boulevard, Chicago, Illinois 60604.</p> <p>The MPCA copy shall be sent to: Air Quality Compliance Tracking Coordinator, Minnesota Pollution Control Agency, 520 Lafayette Road North, St. Paul, MN 55155.</p>	Total Facility

TABLE B: RECURRENT SUBMITTALS

11/07/03

Facility Name: ADM Corn Processing - Marshall

Permit Number: 08300038 - 006

Equipment List	<p>due 30 days after end of each calendar year starting 08/16/2001 . The equipment list shall include a complete description of each piece of equipment described by EU001, EU003, EU004, EU007, EU008, EU064 and EU065. The description shall include the manufacturer, model number, capacity, and date of original installation. The description shall also identify each piece of equipment using a unique identification number.</p> <p>If no equipment changes have been made since submittal of the previous equipment list, then submittal of a new equipment list is not required and only a statement that no equipment changes have been made is required to be submitted.</p>	Total Facility
----------------	---	----------------

Appendix I – Modeled Parameters

Facility: Minnesota Corn Processors

Permit Number: 08300038-006

The following stack parameters were used in the February 29, 2000 model. Revision of any of these parameters must result in plume dispersion characteristics equivalent to or better than the plume dispersion characteristics modeled and summarized in the model dated February 29, 2000. Revision of any of these parameters may require a major amendment.

Table I.1 – Modeled Parameters For Scenario 1: No Operation of SV001

SV ID No.	Modeled Height (feet)	Modeled Diameter ¹ (feet)	Modeled Air Flow (acfm)	Direction of Flow	Modeled Temperature (°F)	Modeled PM ₁₀ (lb/hr)	Modeled SO ₂ (lb/hr)	Modeled NO _x (lb/hr)	Modeled CO (lb/hr)
002	201.12	3.74	40876	Vertical	50	3.62			
003	125.98	1.608	8000*	Horizontal	50	0.71			
004	120.08	1.509	5264	Vertical	50	0.46			
005	45.01	0.394	599	Vertical	50	0.06			
006	195.87	4.003	50059	Vertical	120	6.0	14.97		
007	150.59	4.987	105427	Vertical	100	7.94	23.93		
008	102.36	1.148	4000*	Horizontal	60	0.35			
009	165.03	2.986	17833	Vertical	120	2.5	5.98		
010	149.93	4.003	50059	Vertical	120	6.0	8.98		
011	184.06	8.235	105578	Vertical	150	17.5	15.0	3.07	90.00
012	150.00	1.181	4926	Vertical	350	1.7	1.11	1.87	223.0
013	138.78	2.001	12013	Vertical	350	0.7	2.0	3.38	4.86
014	138.78	2.001	12013	Vertical	350	0.7	2.0	3.38	4.86
015	79.99	1.509	4859	Vertical	89	N/A	0.52		
016	200.13	5.512	74305	Vertical	350	10.81	252.22	68.93	47.94
017	60.04	0.558	188*	Down	50	0.03			
018	60.04	0.656	188*	Horizontal	50	0.03			

SV ID No.	Modeled Height (feet)	Modeled Diameter¹ (feet)	Modeled Air Flow (acfm)	Direction of Flow	Modeled Temperature (°F)	Modeled PM₁₀ (lb/hr)	Modeled SO₂ (lb/hr)	Modeled NO_x (lb/hr)	Modeled CO (lb/hr)
019	150.00	4.987	53329	Vertical	343	1.7	0.30	22.34	28.53
020	150.00	5.315	76343	Vertical	370	2.0	0.40	24.10	38.6
022	14.99	1.247	5527	Vertical	1700	N/A	0.29	0.55	2.96
023	139.11	4.003	38046	Vertical	69	1.71			
024	123.36	0.656	2000*	Horizontal	50	0.18			
025	115.16	0.492	850*	Horizontal	50	0.07			
026	115.16	0.492	850*	Horizontal	50	0.07			
027	115.16	0.492	850*	Horizontal	50	0.07			
028	115.16	0.492	850*	Horizontal	50	0.07			
029	81.04	0.984	1750*	Horizontal	99	0.14			
030	145.01	3.510	37820	Vertical	107	3.57			
031	115.16	0.492	850*	Horizontal	50	0.07			
032	115.16	0.492	850*	Horizontal	50	0.07			
033	68.90	2.001	10013	Vertical	90	0.6	0.49		
034	101.05	4.987	1384	Vertical	60	0.21			
035	34.45	0.427	900*	Horizontal	50	0.08			
036	48.88	0.591	1500*	Down	50	0.13			
037	49.87	0.591	1500*	Down	50	0.13			
038	49.87	0.656	268	Vertical	450	0.01	0.01	0.10	0.04
039	15.42	1.673	922	Vertical	350	0.01	0.01	0.20	0.13
041	80.05	0.427	564	Vertical	50	0.04			
043	95.14	0.492	1356	Vertical	50	0.1			

¹ If the stack is not round (i.e., it is rectangular), this is the equivalent diameter used in the modeling analysis

* This is not the number that was modeled, but is the number supplied by the applicant. When a source exhausts horizontally or downward, the air flow is modeled as a very low number, on the order of zero. However, "0" does not reflect the air flow that the source truly experiences.

Table I.2 – Modeled Parameters For Scenario 2: Operation of SV001

SV ID No.	Modeled Height (feet)	Modeled Diameter ¹ (feet)	Modeled Air Flow (acfm)	Direction of Flow	Modeled Temperature (°F)	Modeled PM ₁₀ (lb/hr)	Modeled SO ₂ (lb/hr)	Modeled NO _x (lb/hr)	Modeled CO (lb/hr)
001	8.0	2.33	12000*	Horizontal	50	0.881			
002	201.12	3.74	40876	Vertical	50	0.00			
003	125.98	1.608	8000*	Horizontal	50	0.71			
004	120.08	1.509	5264	Vertical	50	0.46			
005	45.01	0.394	599	Vertical	50	0.06			
006	195.87	4.003	50059	Vertical	120	6.0	14.97		
007	150.59	4.987	105427	Vertical	100	7.94	23.93		
008	102.36	1.148	4000*	Horizontal	60	0.35			
009	165.03	2.986	17833	Vertical	120	2.5	5.98		
010	149.93	4.003	50059	Vertical	120	6.0	8.98		
011	184.06	8.235	105578	Vertical	150	17.5	15.0	3.07	90.00
012	150.00	1.181	4926	Vertical	350	1.7	1.11	1.87	223.0
013	138.78	2.001	12013	Vertical	350	0.7	2.0	3.38	4.86
014	138.78	2.001	12013	Vertical	350	0.7	2.0	3.38	4.86
015	79.99	1.509	4859	Vertical	89	N/A	0.52		
016	200.13	5.512	74305	Vertical	350	10.81	252.22	68.93	47.94
017	60.04	0.558	188*	Down	50	0.03			
018	60.04	0.656	188*	Horizontal	50	0.03			
019	150.00	4.987	53329	Vertical	343	1.7	0.30	22.34	28.53
020	150.00	5.315	76343	Vertical	370	2.0	0.40	24.10	38.6
022	14.99	1.247	5527	Vertical	1700	N/A	0.29	0.55	2.96
023	139.11	4.003	38046	Vertical	69	1.71			
024	123.36	0.656	2000*	Horizontal	50	0.18			
025	115.16	0.492	850*	Horizontal	50	0.07			
026	115.16	0.492	850*	Horizontal	50	0.07			

SV ID No.	Modeled Height (feet)	Modeled Diameter ¹ (feet)	Modeled Air Flow (acfm)	Direction of Flow	Modeled Temperature (°F)	Modeled PM₁₀ (lb/hr)	Modeled SO₂ (lb/hr)	Modeled NO_x (lb/hr)	Modeled CO (lb/hr)
027	115.16	0.492	850*	Horizontal	50	0.07			
028	115.16	0.492	850*	Horizontal	50	0.07			
029	81.04	0.984	1750*	Horizontal	99	0.14			
030	145.01	3.510	37820	Vertical	107	3.57			
031	115.16	0.492	850*	Horizontal	50	0.07			
032	115.16	0.492	850*	Horizontal	50	0.07			
033	68.90	2.001	10013	Vertical	90	0.6	0.49		
034	101.05	4.987	1384	Vertical	60	0.21			
035	34.45	0.427	900*	Horizontal	50	0.08			
036	48.88	0.591	1500*	Down	50	0.13			
037	49.87	0.591	1500*	Down	50	0.13			
038	49.87	0.656	268	Vertical	450	0.01	0.01	0.10	0.04
039	15.42	1.673	922	Vertical	350	0.01	0.01	0.20	0.13
041	80.05	0.427	564	Vertical	50	0.04			
043	95.14	0.492	1356	Vertical	50	0.1			

¹ If the stack is not round (i.e., it is rectangular), this is the equivalent diameter used in the modeling analysis

* This is not the number that was modeled, but is the number supplied by the applicant. When a source exhausts horizontally or downward, the air flow is modeled as a very low number, on the order of zero. However, "0" does not reflect the air flow that the source truly experiences.

Appendix II -- Insignificant Activities Required to be Listed, and Likely Applicable Requirements

Facility: Minnesota Corn Processors
Permit Number: 08300038-005

Note: Several activities which may ordinarily be listed here as insignificant activities are listed in Table A of the permit, with associated Title I conditions.

Minn. R. 7007.1300, subpart	Rule Description of the Activity, and the Actual Activity	Likely Applicable Requirement
3(A)	Fuel use: space heaters fueled by, kerosene, natural gas, or propane <ul style="list-style-type: none"> • Fifteen (15) natural gas space heater vents 	Minn. R. 7011.0510/0515
3(G)	Emissions from a laboratory, as defined in the subpart. <ul style="list-style-type: none"> • Five (5) QA/QC Lab vents – minimal PM or VOC emissions 	Minn. R. 7011.0710/0715
3(I)	Individual emissions units at a stationary source, each of which have a potential to emit the following pollutants in amounts less than: <ol style="list-style-type: none"> 1. 4,000 lbs/year of carbon monoxide; and 2. 2,000 lbs/year each of nitrogen oxide, sulfur dioxide, particulate matter, particulate matter less than ten microns, volatile organic compounds (including hazardous air pollutant-containing VOC), and ozone. <ul style="list-style-type: none"> • Twenty-three (23) pressure relief valves – minimal emissions of SO₂, VOC or PM • Five (5) chemical room roof vents • Twenty (20) non-VOC storage tanks – minimal emissions of SO₂ or PM (acid mists) • Five (5) miscellaneous vents venting small quantities of SO₂ 	Minn. R. 7011.0710/0715 Minn. R. 7011.0710/0715 Minn. R. 7011.0710/0715 none

TECHNICAL SUPPORT DOCUMENT
For
DRAFT AIR EMISSION PERMIT AMENDMENTS

This technical support document is for all the interested parties of the draft permit amendments. The purpose of this document is to set forth the legal and factual basis for the permit conditions, including references to the applicable statutory or regulatory provisions.

1. General Information

1.1. Table 1 - Permits Being Amended:

Permit No.	Owner/Operator Address	Facility Address
04900065-002	Bergquist Company 5300 Edina Industrial Boulevard Edina, MN 55439	301 West Washington Street Cannon Falls Goodhue County
16300003-008	Marathon Ashland Petroleum LLC PO Box 9 459 3 rd Avenue St. Paul Park, MN 55071	Marathon Ashland Petroleum LLC 459 3 rd Avenue St. Paul Park, MN 55071
01700002-007	Sappi Cloquet LLC PO Box 503 2201 Avenue B Cloquet, MN 55720	Sappi Cloquet LLC 2201 Avenue B Cloquet, MN 55720
08300038-006	ADM Corn Processing – Marshall 901 Highway 59 Marshall, MN 56258	ADM Corn Processing – Marshall 400 West Erie Road Marshall, MN 56258
13700005-002	US Steel Minn Ore Operations – Minntac PO Box 417 Mountain Iron, MN 55768	US Steel Minn Ore Operations – Minntac 8819 Old Highway 169 Mountain Iron, MN 55768

1.2. Reason for Permit Actions

These permit amendments are Minnesota Pollution Control Agency (MPCA) initiated major amendments under Minn. R. 7007.1600, subp. 1(D); mandatory reopenings that are needed in order to assure compliance with applicable requirements.

The amendments incorporate new or revised limits into the referenced permits. The limits have been imposed through performance testing under Minn. R. 7017.2025, subp. 3 and are already in affect. The permits must be reopened in order to reflect the revised limits.

These amendments are from MPCA letters sent between October 1, 2002, and June 30, 2003, that set new limits in Part 70 permits based on performance testing under Minn. R. ch. 7017.

1.3. Change in Emissions

There are no changes in emissions associated with the permit reopenings.

1.4 Comments on Draft Permit for ADM Corn Processing – Marshall

The permittee submitted comments on the draft permit. All comments were resolved. One comment corrected an erroneous reference to a different facility. The other comment addressed the increased production limit. The draft permit stated that the production limit set as a result of performance testing would be increased to 20,832 lb/hr, whereas the letter of compliance from performance testing stated that the production limit should be increased to 30,910 lb/hr. The emission limit for the stack is not affected by the production limit, nor is it relied upon for determination of applicable requirements. The permit now states that the new production limit is 30,910 lb/hr.

2. Regulatory and/or Statutory Basis

The following table shows which permit limits were revised in each permit, as well as the date of the MPCA letter that sets the new limits. See Attachment 1 to this TSD for a copy of the letters.

Table 2 Regulatory Overview

Permit No.	Level	Old/New Limits	Basis
16300003-007 (Marathon Ashland Petroleum LLC)	EU022	Old: Performance Test frequency based on a 36-month basis, but still included date for annual testing. New: Removed obsolete requirement to test by 3/31/03 (test conducted).	August 16, 2002, letter from MPCA implementing Minn. R. 7017.2025, subp. 3
16300003-007 (Marathon Ashland Petroleum LLC)	EU025	Old: Fuel Usage limit of 25.7 MMBtu/hr based on an 8-hour block average... New: Fuel Usage limit of 24.5 MMBtu/hr based on an 8-hour block average...	June 17, 2003, letter from MPCA implementing Minn. R. 7017.2025, subp. 3

16300003-007 (Marathon Ashland Petroleum LLC)	EU026	Old: Fuel Usage limit of 32.8 MMBtu/hr based on an 8-hour block average... New: Fuel Usage limit of 46 MMBtu/hr based on an 8-hour block average...	November 19, 2002, letter from MPCA implementing Minn. R. 7017.2025, subp. 3
04900065-002 (Bergquist Co. – Cannon Falls)	CE001	Old: Thermal Oxidizer Temperature $\geq 1400^{\circ}\text{F}$ New: Thermal Oxidizer Temperature $\geq 1350^{\circ}\text{F}$	November 22, 2002 letter from MPCA implementing Minn. R. 7017.2025, subp. 3
04900065-002 (Bergquist Co. – Cannon Falls)	CE002	Old: Thermal Oxidizer Temperature $\geq 1400^{\circ}\text{F}$ New: Thermal Oxidizer Temperature $\geq 1225^{\circ}\text{F}$	November 22, 2002 letter from MPCA implementing Minn. R. 7017.2025, subp. 3
04900065-002 (Bergquist Co. – Cannon Falls)	CE003	Old: Thermal Oxidizer Temperature $\geq 1400^{\circ}\text{F}$ New: Thermal Oxidizer Temperature $\geq 1250^{\circ}\text{F}$	November 22, 2002 letter from MPCA implementing Minn. R. 7017.2025, subp. 3
04900065-002 (Bergquist Co. – Cannon Falls)	CE004	Old: Thermal Oxidizer Temperature $\geq 1400^{\circ}\text{F}$ New: Thermal Oxidizer Temperature $\geq 1225^{\circ}\text{F}$	November 22, 2002 letter from MPCA implementing Minn. R. 7017.2025, subp. 3
08300038-006 (ADM Corn Processing – Marshall)	SV011	Old: Process throughput $\leq 20,613$ lb/hr using 30-day rolling average... New: Process throughput $\leq 30,910$ lb/hr using 30-day rolling average...	November 6, 2002 letter from MPCA implementing Minn. R. 7017.2025, subp. 3
08300038-006 (ADM Corn Processing – Marshall)	SV011	Old: Performance Test: due before end of each 36 months starting 12/03/2003 to measure (1) NO _x and (2) CO emissions at the stack. The first test is due December 6, 2003, then every 36 months thereafter. New: Performance Test: due	Clarification in permit that required testing has been completed.

		before end of each 36 months starting 9/02/2002 to measure (1) NOx and (2) CO emissions at the stack. Initial performance testing was completed 9/02/2002.	
--	--	--	--

01700002-007 (Sappi Cloquet LLC)	EU002	Old: Steam Generation: ≤ 194,260 lb/hr using 8-hr block average... New: Steam Generation: ≤ 203,720 lb/hr using 8-hr block average...	June 5, 2003 letter from MPCA implementing Minn. R. 7017.2025, subp. 3
01700002-007 (Sappi Cloquet LLC)	EU002	Old: Wood/bark Usage: ≤ 24.2 tons/hr using 8-hr block average... New: Wood/bark Usage: ≤ 22.2 tons/hr using 8-hr block average...	June 5, 2003 letter from MPCA implementing Minn. R. 7017.2025, subp. 3
13700005-002 (US Steel Minn Ore Operations – Minntac)	SV122	Old: No operating limit New: Liquid Flow Rate: ≥ 270 gallons/minute using 8-hr block average...	May 16, 2003 letter from MPCA implementing Minn. R. 7017.2025, subp. 3

3. Contact

MPCA staff contact for these Permit Actions: Bonnie J. Nelson

Attachment No. 1: MPCA Performance Test Letters with corresponding permit changes.

Attachment No. 2: Comment letter from ADM with corresponding permit changes.

Attachment 1

Letters of Compliance with corresponding permit changes

Attachment 2

Comment letter from ADM with corresponding permit changes